

USA

AVANT[®]

Loaders and attachments



25
YEARS

Revision A

Foreword

This catalog contains most of the Avant attachments available from Avant Tecno USA at the date of printing.

Avant has a policy of continuing product development and retains the right to change specifications without notice.

All attachments listed in this catalog may not be available in all markets and countries, please consult your local Avant dealer.

Operation of certain attachments may require specific equipment on the loader. Please consult your local Avant dealer.

Compatibility tables between attachments and loader models are advisory. All attachments do not fit on all loader models. Please contact your local Avant dealer to make sure that the attachment is compatible with your Avant loader.

Table of Contents

LOADERS

Loaders and options.....4-31

| | |
|-----------------|----|
| 200 series..... | 4 |
| 400 series..... | 8 |
| 500 series..... | 14 |
| 600 series..... | 20 |
| 700 series..... | 26 |

ATTACHMENTS

Buckets, material handling.....32-48

| | |
|----------------------------------|----|
| General bucket..... | 32 |
| Heavy duty general bucket..... | 33 |
| Light material bucket..... | 34 |
| XL Light material bucket..... | 35 |
| 4 in 1 bucket..... | 36 |
| High tip bucket..... | 37 |
| XL high tip bucket..... | 38 |
| Grapple bucket..... | 39 |
| Demolition grapple bucket..... | 40 |
| leveling bucket..... | 41 |
| Pallet fork..... | 42 |
| Pallet fork with side shift..... | 43 |
| Skip bucket..... | 44 |
| Jib boom..... | 45 |
| Telescoping jib boom..... | 46 |
| Ball hitch on front..... | 47 |

| | |
|------------------------------|----|
| Hydraulic trailer hitch..... | 48 |
| Site toolbox..... | 48 |

Property maintenance.....49-70

| | |
|-------------------------------------|----|
| Dozer blade 1400..... | 49 |
| Dozer blade 2000..... | 50 |
| Dozer blade 2500..... | 51 |
| Snow plow..... | 52 |
| V-Snow blade..... | 53 |
| Flipper bucket..... | 54 |
| Snow blower 1100..... | 55 |
| Snow blower..... | 56 |
| Rotary broom..... | 57 |
| Collecting broom 1500..... | 58 |
| Collecting broom 1050..... | 59 |
| Bucket broom..... | 60 |
| High pressure washer..... | 61 |
| Artificial turf attachment..... | 62 |
| Turf pusher..... | 63 |
| Sand/salt spreader..... | 64 |
| Centrifugal sand/salt spreader..... | 65 |
| Towable sand spreader..... | 66 |
| Vacuum brush..... | 67 |
| Leguan 50 Access platform..... | 68 |
| Tipping trailer..... | 69 |
| Trailer/Timber trailer..... | 70 |

| | | | |
|--|----------------|--|----------------|
| Groundcare..... | 71-80 | Carousel broom..... | 111 |
| Lawn mower 1200..... | 71 | Round bale grab..... | 112 |
| Lawn mower 1500..... | 72 | Square bale grab..... | 113 |
| Collecting lawn mower 1200..... | 73 | Bale handler..... | 114 |
| Collecting lawn mower 1500..... | 74 | Bale fork..... | 115 |
| Flail mower..... | 75 | Round bale splitter..... | 116 |
| Cutting bar..... | 76 | Bedding distributor bucket..... | 117 |
| Fingerbar mower with hydraulic boom..... | 77 | Manure fork..... | 118 |
| Flail mower with hydraulic boom..... | 78 | Grain/flour dispenser bucket..... | 118 |
| Edge trimmer..... | 79 | Push broom..... | 119 |
| Weed brush..... | 80 | 3-point hitch adapter..... | 120 |
| Landscaping..... | 81-92 | Horse manure collector..... | 121 |
| Rotary hoe..... | 81 | Front cultivator..... | 122 |
| Stone burier..... | 82 | Horse arena harrow..... | 123 |
| Rotary harrow..... | 83 | Big bag transporter..... | 124 |
| Leveler..... | 84 | Stone collecting bucket..... | 125 |
| Front rake..... | 85 | PowerPacks..... | 126-127 |
| Ripper..... | 86 | Compressor..... | 126 |
| Screening bucket..... | 87 | Pressure washer..... | 127 |
| Stump grinder..... | 88 | Handheld tools..... | 128-129 |
| Stump buster..... | 89 | Rock drill..... | 128 |
| Stone grab..... | 90 | Hydraulic breaker..... | 128 |
| Stone installation clamp..... | 91 | Core drill..... | 129 |
| Grabbing tool..... | 92 | Cut-off saw..... | 129 |
| Digging and construction..... | 93-104 | Forestry..... | 130-134 |
| Backhoe 170..... | 93 | Winch..... | 130 |
| Backhoe 210..... | 94 | Tree shear..... | 131 |
| Backhoe 260..... | 95 | Log grab, heavy duty..... | 132 |
| Mini digger..... | 96 | Log grab..... | 133 |
| Trencher..... | 97 | Timber grab..... | 134 |
| Auger..... | 98 | Options..... | 135-137 |
| Hydraulic breaker..... | 99 | Tilt adapter..... | 135 |
| Cutter crusher C290..... | 100 | Receiver hitch..... | 135 |
| Concrete mixing bucket..... | 101 | Adapter plate..... | 136 |
| Drum type concrete mixer..... | 102 | Skid-Steer Attachment Mounting Adapters..... | 136 |
| Disc scraper..... | 102 | Attachment control switch pack..... | 137 |
| Vibrating plate..... | 103 | Tie down bracket..... | 137 |
| Asphalt grinder..... | 103 | Additional products..... | 138 |
| Submersible pump..... | 104 | Filter kits..... | 139 |
| Farming and horse stables..... | 104-125 | Multi-connector System..... | 139 |
| All-round grapple..... | 104 | Wheels and tires..... | 140 |
| Silage fork..... | 105 | | |
| XL silage grab..... | 106 | | |
| Feeding table cleaning blade..... | 107 | | |
| Silage dispenser..... | 108 | | |
| Feed mover screw..... | 109 | | |
| Silage block cutter..... | 110 | | |

200 series

200 series



| Model | AVANT 220 | AVANT 225 | AVANT 225 LPG |
|---------------------------------|--------------------------|--------------------------|--------------------------|
| Length | 75.2 in | 75.2 in | 76.4 in |
| Width* | 39.2 in | 39.2 in | 39.2 in |
| Height | 74 in | 74 in | 74 in |
| Weight | 1540 lb | 1540 lb | 1540 lb |
| Wheels | 20x8.00-10 tractor/grass | 20x8.00-10 tractor/grass | 20x8.00-10 tractor/grass |
| Transmission, drive | hydrostatic | hydrostatic | hydrostatic |
| Pulling force | 1395 lbf | 1440 lbf | 1440 lbf |
| Drive speed (max.) | 6.2 MPH | 6.2 MPH | 6.2 MPH |
| Auxiliary hydraulics | 7.9 gal/min/2680 PSI | 11.1 gal/min/2680 PSI | 11.1 gal/min/2680 PSI |
| Hydraulic oil cooler | standard | standard | standard |
| Turning radius inside/outside** | 35.8 / 75.2 in | 35.8 / 75.2 in | 35.8 / 75.2 in |
| Tipping load*** | 772 lb | 772 lb | 772 lb |
| Engine | Kohler CV640 | Kohler ECV730 EFI | Kohler PCV740 EFI |
| Engine output | 20 hp | 25 hp | 25 hp |
| Fuel | Gasoline | Gasoline | Propane |
| Product no: | A21675 | A21687 | A21695 |

* 40.4 in. with optional wheel spacers

** Turning radius with Standard tires

*** Load is measured at 15.8 in from the attachment coupling plate.

200 series standard features

Standard specification

- Hydraulic multi-connector
- Self leveling boom
- Reverse beeper
- Drive release valve
- Joystick, 4-function (220)
- Joystick, 6-function (225)
- Hydraulic oil cooler
- ROPS with FOPS canopy
- 2 front headlights
- Manual parking brake
- Hydrostatic direct 4WD with 4 drive motors
- Standard tires 20x8.00-10 tractor or grass profile
- Wheel weights
- Rear trailer hitch with 2-inch ball
- Heated suspension seat with arm rests and seat belt
- 4.7 gal fuel tank
- 6.1 gal hydraulic oil tank

200 series options



- A36785** 6-way Joystick control (optional 220, standard 225)
- Auxiliary hydraulics control with buttons on the joystick



- A36880** Attachment control switch pack
- Controls electric functions for specific attachments
 - Consists of 3 pcs control switches, wiring and a 7-pole socket which mounts in the auxiliary hydraulics multi-connector.



- A36679** Adapter for attachment's electric connector
- converting the old electricals to fit the new multi-connector. If the loader is equipped with the electric socket integrated into the multi-connector, the attachment connector can be fitted with adapter A36679.



- A36681** Cab L
- Windscreen (equipped with wiper and washer), right side window and rear window.



- A36866** Work light kit: 2 front, 1 rear (LED, 700 lumen)



- A36773** Traffic Kit
- Headlights, turn signals, reflectors, beacon, 4-way hazards



- A421008** Beacon

200 series options




A49548 Anti slip valve



A421206 Boom floating (factory installed only)



PTBH-200 Engine heater



A36871 Auxiliary hydraulics outlet in the rear
• double acting



A46584 Wheel weight 31 lb (incl. 2 wheelnuts) (standard)



A44337 Wheel spacer, 0.6 in, 4-bolt rim



A37093 Hand drive controls
• With this system you can operate the forward-reverse drive from a switch on the joystick or use the standard pedals. Selection between hand drive and drive pedals is as easy as a flip of a switch on the dashboard.



65434 Weather cover for 200 series
• Covers the loader's interior, protects against rain, snow etc.
• Integrated storage pouch, mounts on the safety frame



65477 Full weather cover 200 series
• Protects the entire Avante loader
• HD storage bag

400 series

400 series



Width

| Wheel size | Profile | Machine width |
|-----------------|-------------|---------------|
| 5 x 10 | TR | 39.0 in |
| 23 x 8.50 - 12 | TR or grass | 41.3 in |
| 23 x 10.50 - 12 | TR or grass | 43.1 in |

| Model | AVANT 420 |
|--|-------------------------|
| Length | 86.4 in |
| Width | 39.0 - 43.1 in |
| Height | 78 in |
| Weight | 2270 lb |
| Standard wheels | 23x8.50-12" TR or grass |
| Transmission, drive | hydrostatic |
| Pulling force | 1500 lbf |
| Drive speed (max.) | 7.5 MPH |
| Auxiliary hydraulics oil flow / pressure | 8.2 gal/min 2680 PSI |
| Hydraulic oil cooler | Standard |
| Turning radius inside/outside* | 34.6 / 77.6 in |
| Tipping load** | 1210 lb |
| Max. breakout force | 1430 lbf |
| Engine make and type | Kubota D722 |
| Engine output | 20 hp |
| Fuel | Diesel |
| Product no: | A21 358 |

* Turning radius with Standard tires

** Load is measured at 15.8 in from the attachment coupling plate, unit with rear sideweights.

400 series features

Standard specification

- Telescopic Boom
- Hydraulic multi-connector system
- Reverse beeper
- Drive release valve
- Joystick, 4-function
- Hydraulic oil cooler
- ROPS with FOPS canopy
- 2 front head lights
- Manual parking brake
- Hydrostatic direct 4WD with 4 drive motors
- Standard tires 23x8.50-12 Tractor or Grass profile
- Heated suspension seat with arm rests and seat belt
- 5.3 gal fuel tank
- 10 gal hydraulic oil tank

NOTE: Self leveling boom is not available on 400 series

Avant 420 benefits over 220

- Handling force +450 lb
- Lifting height +55 inch
- Driving speed +1.3 MPH
- Greater pulling force
- More spacious cockpit

400 series options



- A35479** 6-way joystick control
- Auxiliary hydraulics control with buttons on the joystick



- A36878** Attachment control switch pack
- Controls electric functions for specific attachments
 - Consists of 3 pcs control switches, wiring and a 7-pole socket which mounts on the auxiliary hydraulics multi-connector.



- A36679** Adapter for attachment's electric connector
- converting the old electricals to fit the new multi-connector. If the loader is equipped with the electric socket integrated into the multi-connector, the attachment connector can be fitted with adapter A36679.



- A34624** Cab L
- Windscreen (equipped with wiper and washer), right side window and rear window.



- MCSD400** Cab L - soft side door
- Snap-on, zipper door to enclose cab L entry and exit.



- A33916** Work light kit: 2 front, 1 rear (LED, 700 lumen)
A34917 Work light kit: 2 front, 1 rear (LED, 2500 lumen)



- A34614** Traffic Kit
- Headlights, turn signals, reflectors, beacon, 4-way hazards

400 series options



A34002 Beacon



A34753 Anti-slip valve



A47773 Boom floating



PTBH-SM Engine block heater



A410226 Exhaust purifier (420)



A34636 Auxiliary hydraulics outlet in the rear,
single acting

A34632 Auxiliary hydraulics outlet in the rear,
double acting



A35504 Extra aux. hydr. double acting outlet front, 400 series
For customers who want to mount the tilt adapter
(must be equipped with conventional type quick cou-
plers) and a hydraulic attachment – like 4 in 1 bucket
- on the machine at the same time.



A35662 Cover plates
• Heavy duty (polycarbonate)

400 series options



A36572 Rear guard

A rear guard protecting the rear part of machine and radiator. The rear guard has tie down brackets integrated and it is possible to mount any trailer hitch or backweight onto a machine equipped with a rear guard. Rear guard is bolt mounted and can be easily retrofitted or later taken off if necessary.



A418746 Tie down bracket

A simple bracket, that makes it easier to tie down machines during transport. Fits either to the back of the machine or to side of rear frame. Can be mounted also between rear frame and trailer coupling or to rear back weight with handle, which allows the use of it even if a trailer coupling is mounted



A417337 Trailer ball hitch 2 inch with towing pin HH2INREC 2" Receiver hitch with tie down rings



A36401 Rear side weight kit 176 lbs



A35957 Extra back weight with handle, 64 lbs



- MW6.510T Wheel kit 5 x 10 TR
- MW6.2310512T Wheel kit 23 x 10.50 - 12 TR
- MW6.2310512G Wheel kit 23 x 10.50 - 12 grass


400 series options



- 65436 Weather cover for 400 - 700 series
- Covers the loader's interior, protects against rain, snow etc.
 - Integrated storage pouch, mounts on the ROPS frame



- 65478 Full weather cover for 400, 500 and 600 series
- Protects the entire Avant loader
 - HD storage bag



- 64055 Snow chains, pair, 5 x 10 TR pic. 1
64746 Snow chains, pair, 23 x 8.50 -12 pic. 1
64455 Snow chains, pair, 23 x 8.50 -12 pic. 2
64745 Snow chains, pair, 23 x 10.50 -12 pic. 2

Additional attachment options in back of catalog

500 series



Width

| Wheel size | Profile | Machine width |
|-----------------|-------------|---------------------|
| 27 x 8.50 - 15 | TR | 40.6 in/ 44.6 in |
| 23 x 8.50 - 12 | TR or grass | 42.5 in |
| 23 x 10.50 - 12 | TR or grass | 44.5 in |
| 26 x 12.00 - 12 | TR or grass | 50.8 in |

| Model | AVANT 520 | AVANT 528 |
|--|--------------------------|--------------------------|
| Length | 95.7 in | 100.4 in |
| Width (with 23x10.50-12 wheels) | 44.5 in | 44.5 in |
| Height | 78.2 in | 78.2 in |
| Weight | 2910 lb | 3130 lb |
| Standard wheels | 23x10.50-12" TR or grass | 23x10.50-12" TR or grass |
| Transmission, drive | hydrostatic | hydrostatic |
| Pulling force | 1985 lbf | 2100 lbf |
| Drive speed (max.) | 7.5 MPH | 7.5 MPH |
| Auxiliary hydraulics oil flow / pressure | 8.2 gal/min 2680 PSI | 9.5 gal/min 2900 PSI |
| Hydraulic oil cooler | Standard | Standard |
| Turning radius inside/outside* | 39.2 / 80.7 in | 39.2 / 80.7 in |
| Max. lifting height | 109.8 in | 109.8 in |
| Tipping load** | 1900 lb | 2360 lb |
| Max. breakout force | 2400 lb | 2800 lb |
| Engine make and type | Kubota D722 | Kubota D1105 |
| Engine output | 20 hp | 25 hp |
| Fuel | Diesel | Diesel |
| Product no: | A21660 | A21658 |

* Turning radius with 23x10.50-12 wheels

** Load is measured at 15.8 in from the attachment coupling plate, unit with rear sideweights.

500 series features

Standard specification

- Telescopic Boom
- Self leveling boom
- Hydraulic multi-connector system
- Reverse beeper
- Drive release valve
- Joystick, 4-function
- Hydraulic oil cooler
- ROPS with FOPS canopy
- 2 front head lights
- Toggle switch, hydraulic parking brake
- Hydrostatic direct 4WD with 4 drive motors
- Standard tires 23x10.50-12 Tractor or Grass profile
- Heated suspension seat with arm rests and seat belt
- Integrated back weight 375 lb
- Fuel tank size 520 = 5.2 gal ; 528 = 7.9 gal
- 10 gal hydraulic oil tank

Avant 500 series advantages over 400 series

- More lift capacity and handling power
- LX Cab with heater available
- Self leveling boom

500 series options



- A35754 6-way joystick control**
- Auxiliary hydraulics control with buttons on the joystick



- A36878 Attachment control switch pack**
- Controls electric functions for specific attachments
 - Consists of 3 pcs control switches, wiring and a 7-pole socket which mounts on the auxiliary hydraulics multi-connector.



- A36679 Adapter for attachment's electric connector**
- converting the old electricals to fit the new multi-connector. If the loader is equipped with the electric socket integrated into the multi-connector, the attachment connector can be fitted with adapter A36679.



- A21592 Cab L**
- Windscreen (equipped with wiper and washer), right side window and rear window.



- MCSD500U Cab L - soft side door**
- Snap-on, zipper door to enclose cab L entry and exit.



- A21517 Cab LX**
- Windscreen (equipped with wiper), right side window and rear window
 - Door, heater and front mudguards
- A35352 Road traffic light kit**
- Headlights, turn signals, reflectors, beacon, 4-way hazards

500 series options



- A33916 Work light kit: 2 front, 1 rear (LED, 700 lumen)
A34917 Work light kit: 2 front, 1 rear (LED, 2500 lumen)



- A35732 Work light kit: 2 front, 1 rear (LED, 700 lumen)
on cab LX
A35731 Work light kit: 2 front, 1 rear (LED, 2500 lumen)
on cab LX



- A33912 Road traffic light kit, on ROPS frame
- Headlights, turn signals, reflectors, beacon, 4-way hazards



- A34002 Beacon



- A35506 Anti slip valve



- A34015 Boom floating



- PTBH-SM Engine block heater (520)
PTBH-MD Engine block heater (528)



- A35513 Exhaust purifier, (528)
A410226 Exhaust purifier, (520)

500 series options



A35882 Auxiliary hydraulics outlet in the rear, single acting

A35881 Auxiliary hydraulics outlet in the rear, double acting



A35884 Extra aux. hydr. outlet front

For customers who want to mount the tilt adapter (must be equipped with conventional type quick couplers) and a hydraulic attachment – like 4 in 1 bucket – on the machine at the same time.



A36079 Cover plates HD, 520, machine with ROPS frame

A35666 Cover plates HD, 520, machine with cab LX

A36080 Cover plates, HD, 528, machine with ROPS frame

A36081 Cover plates, HD, 528, machine with ROPS & mudguards rear

A35670 Cover plates, HD, 528, machine with cab LX

A35669 Cover plates, HD, 528, machine with LX & mudguards rear

- Heavy duty (polycarbonate)



A418746 Tie down bracket

A simple bracket, that makes it easier to tie down machines during transport. Fits either to the back of the machine or to side of rear frame. Can be mounted also between rear frame and trailer coupling or to rear back weight with handle, which allows the use of it even if a trailer coupling is mounted



A36572 Rear guard

A rear guard protecting the rear part of machine and radiator. The rear guard has tie down brackets integrated and it is possible to mount any trailer hitch or backweight onto a machine equipped with a rear guard. Rear guard is bolt mounted and can be easily retrofitted or later taken off if necessary.



A417337 Trailer ball hitch 2 inch with towing pin

HH2INREC 2" Receiver hitch with tie down rings



A36401 Rear side weight kit 176 lbs

500 series options



A49063 Rear side weight kit 400 lb (528 only)



A35957 Extra back weight with handle, 64 lbs



MW10.261212G 26 x 12.00 - 12 grass

MW10.261212T 26 x 12.00 - 12 TR

MW10.278515T 27 x 8.50 - 15 TR



65436 Weather cover for 400 - 700 series

- Covers the loader's interior, protects against rain, snow etc.
- Integrated storage pouch, mounts on the ROPS frame



65478 Full weather cover for 400, 500 and 600 series

- Protects the entire Avant loader
- HD storage bag



64746 Snow chains, pair, 23 x 8.50 - 12 pic.1

64455 Snow chains, pair, 23 x 8.50 - 12 pic.2

64745 Snow chains, pair, 23 x 10.50 - 12 pic.2

64973 Snow chains, pair, 26 x 12.00 - 12 pic.2

65603 Snow chains, pair, 320/60-12 pic.2

65723 Snow chains, pair, 27 x 8.50-15 pic.1

Additional attachment options in back of catalog

600 series

600 series



Height with Cab

| Wheel size | 26x12.00-12 or 320/60-12 | 27x8.50-15 |
|---|--------------------------|------------|
| Cab LX | 79.7 in | 80.2 in |
| Cab DLX | 80.5 in | 81.0 in |
| Cab DLX with Air conditioning on the roof | 85.9 in | 86.4 in |

Width

| Wheel size | Profile | Machine width |
|-----------------|-------------|--------------------|
| 27 x 8.50 - 15 | TR | 40.6 in 44.6 in |
| 26 x 12.00 - 12 | TR or grass | 50.8 in |
| 320/60 - 12 | TR | 50.8 in |

| Model | AVANT 630 | AVANT 635 | AVANT 640 |
|--|--------------------------|--------------------------|--------------------------|
| Length | 100.3 in | 100.3 in | 100.3 in |
| Width (with 26x12.00-12 wheels) | 50.8 in | 50.8 in | 50.8 in |
| Height | 81.5 in | 81.5 in | 81.5 in |
| Weight | 3310 lb | 3370 lb | 3500 lb |
| Standard wheels | 26x12.00-12" TR or grass | 26x12.00-12" TR or grass | 26x12.00-12" TR or grass |
| Transmission, drive | hydrostatic | hydrostatic | hydrostatic |
| Pulling force | 2650 lbf | 2650 lbf | 3100 lbf |
| Drive speed (max.) | 9 MPH | 9 MPH | 14 MPH |
| Auxiliary hydraulics oil flow / pressure | 11.6 gal/min 2900 PSI | 17.4 gal/min 2900 PSI | 17.4 gal/min 2900 PSI |
| Hydraulic oil cooler | Standard | Standard | Standard |
| Turning radius inside/outside* | 35.4 / 97.2 in | 35.4 / 97.2 in | 35.4 / 97.2 in |
| Max. lifting height | 112 in | 112 in | 112 in |
| Max. tipping load** | 2440 lb | 2560 lb | 2620 lb |
| Max. breakout force | 2760 lbf | 2760 lbf | 2760 lbf |
| Engine make and type | Kubota D 1105 | Kubota V1505 | Kubota V1505 |
| Engine output | 25 hp | 37.5 hp | 37.5 hp |
| Fuel | Diesel | Diesel | Diesel |
| Product no: | A21618 | A21561 | A21581 |

* Turning radius with 26x12.00-12 wheels

** Load is measured at 15.8 in from the attachment coupling plate, unit with rear sideweights.

600 series features

Standard specification

- Telescopic Boom
- Self leveling boom
- Hydraulic multi-connector system
- Reverse beeper
- Drive release valve
- Joystick, 8-function
- Toggle switch, hydraulic parking brake
- High volume hydraulic oil cooler
- ROPS with FOPS canopy
- 2 front head lights
- Hydrostatic direct 4WD with 4 drive motors
- Dual speed up to 14 mph (640)
- Standard tires 26x12-12 Tractor or Grass profile
- Heated suspension seat with arm rests and seat belt
- Integrated back weight 375 lb
- Fuel tank size 7.9 gal.
- 10 gal hydraulic oil tank

Avant 600 series advantages over 500 series

- More lift capacity and handling power
- Stronger and faster hydraulic system
- 8-way joystick control
- More oil flow for attachments,
Dual pump with 11.6 gal/min (630) / 17.4 gal/min (635/640)
- More handling power
- DLX Cab with Heat and A/C available (635/640)

600 series options



- A36878** Attachment control switch pack
- Controls electric functions for specific attachments
 - Consists of 3 pcs control switches, wiring and a 7-pole socket which mounts on the auxiliary hydraulics multi-connector.



- A36679** Adapter for attachment's electric connector
- converting the old electricals to fit the new multi-connector. If the loader is equipped with the electric socket integrated into the multi-connector, the attachment connector can be fitted with adapter A36679.



- A21592** Cab L
- Windscreen (equipped with wiper and washer), right side window and rear window.



- MCSD500U** Cab L - soft side door
- Snap-on, zipper door to enclose cab L entry and exit.



- A21517** Cab LX
- Windscreen (equipped with wiper and washer), right side window and rear window.
 - Door, heater and front mudguards

- A35352** Road traffic light kit
- Headlights, turn signals, reflectors, beacon, 4-way hazards



- A21463** Cab DLX, AC (Unit position rear) 635, 640 only
- A21511** Cab DLX, AC (Unit position roof) 635, 640 only
- Heater and noise isolating interior
 - Traffic kit
 - Work light kit
 - heated fabric seat with arm rests and seat belt, radio and cab air filter
 - Front and rear mudguards
- A413706** Heated fabric air suspended seat, with arm rest and seat belt -fitted only in DLX cabs

600 series options



A33916 Work light kit: 2 front, 1 rear (LED, 700 lumen)
on ROPS

A34917 Work light kit: 2 front, 1 rear (LED, 2500 lumen)
on ROPS



A35732 Work light kit: 2 front, 1 rear (LED, 700 lumen)
on cab LX

A35731 Work light kit: 2 front, 1 rear (LED, 2500 lumen)
on cab LX



A33912 Road traffic light kit, on ROPS frame

- Headlights, turn signals, reflectors, beacon, 4-way hazards



A34002 Beacon



A36739 Beacon light bar

- Only for DLX cabs
- Gives more light than the std. beacon
- Visible from behind cab with A/C on the roof



A35506 Anti slip valve

A35830 Smooth drive (640)

only with boom float and self-leveling



A34015 Boom floating



PTBH-MD Engine block heater



A35513 Exhaust purifier

600 series options



A34014 Auxiliary hydraulics outlet in the rear, single acting

A47774 Auxiliary hydraulics outlet in the rear, double acting



A35462 Extra aux. hydr. outlet front

For customers who want to mount the tilt adapter (must be equipped with conventional type quick couplers) and a hydraulic attachment – like 4 in 1 bucket - on the machine at the same time.



A36080 Cover plates, HD, machine with ROPS frame

A36081 Cover plates, HD, machine with ROPS & mudguards rear

A35670 Cover plates, HD, machine with cab LX/DLX

A35669 Cover plates, HD, machine with LX/DLX & mudguards rear
• Heavy duty (polycarbonate)



A418746 Tie down bracket

A simple bracket, that makes it easier to tie down machines during transport. Fits either to the back of the machine or to side of rear frame. Can be mounted also between rear frame and trailer coupling or to rear back weight with handle, which allows the use of it even if a trailer coupling is mounted



A36572 Rear guard

A rear guard protecting the rear part of machine and radiator. The rear guard has tie down brackets integrated and it is possible to mount any trailer hitch or backweight onto a machine equipped with a rear guard. Rear guard is bolt mounted and can be easily retrofitted or later taken off if necessary.



A417337 Trailer ball hitch 2 inch with towing pin

HH2INREC 2" Receiver hitch with tie down rings



A36401 Rear side weight kit 176 lbs

600 series options



A49063 Rear side weight kit 400 lb



A35957 Extra back weight with handle, 64 lbs



MW10.261212G 26x12.00-12 grass
MW10.278515T 27x8.50-15 TR add. price
MW10.3206012T 320/60-12 HD TR add. price



65436 Weather cover for 400 - 700 series

- Covers the loader's interior, protects against rain, snow etc.
- Integrated storage pouch, mounts on the ROPS frame



65478 Full weather cover for 400, 500 and 600 series

- Protects the entire Avant loader
- HD storage bag



64745 Snow chains, pair, 23 x 10.50 -12 pic.2
64973 Snow chains, pair, 26 x 12.00 -12 pic.2
65603 Snow chains, pair, 320/60-12 pic.2
65723 Snow chains, pair, 27 x 8.50-15 pic.1

Additional attachment options in back of catalog

700 series

700 series



Width

| Wheel size | Profile | Machine width |
|----------------|----------|---------------|
| 400/50 - 15 | TR/Grass | 57.1 in |
| 31 x 15.5 - 15 | Grass | 55.9 in |
| 27 x 8.5 - 15 | TR | 42.5 in |
| | | 46.6 in |

| Model | AVANT 755i | AVANT 760i |
|----------------------------------|--------------------------------------|-----------------------|
| Length | 120.5 in | 120.5 in |
| Width (standard tires) | 51 in | 57.1 in |
| Height | 81.1 in | 83.1 in |
| Weight, starting from | 4420 lb | 4640 lb |
| Standard tires | 26/12.00-12 Grass, 320/60-12 Tractor | 400/50-15 TR or grass |
| Transmission | Hydrostatic | Hydrostatic |
| Pulling force | 2990 lbf | 3600 lbf |
| Drive speed | 10.5 mph | 18.6 mph |
| Auxiliary hydraulics | 21.1 gal/min 3260 PSI | 21.1 gal/min 3260 PSI |
| Turning radius (inside/outside)* | 49.2 / 105.3 in | 49.2 / 105.3 in |
| Lifting height | 122.0 in | 122.0 in |
| Tipping load** | 3810 lb | 3810 lb |
| Max. breakout force at 20 in | 3750 lbf | 3750 lbf |
| Engine make and type | Kohler KDI 1903 TCR | Kohler KDI 1903 TCR |
| Engine output | 57 hp | 57 hp |
| Fuel | diesel | diesel |
| Product no: | A21674 | A21647 |

* With standard wheels

** Load is measured at 15.8 in from the attachment coupling plate, unit with rear sideweights.

| Height with Cab | 26x12.00-12 and 320/60-12 | 320/55-15 | 400/50-15 and 31x15.5-15 |
|---|---------------------------|-----------|--------------------------|
| Cab LX | 81.8 in | 83.1 in | 83.9 in |
| Cab DLX | 82.9 in | 84.2 in | 85.4 in |
| Cab DLX with Air conditioning on the roof | 88.2 in | 89.6 in | 90.7 in |

700 standard features

Standard specification

- Telescopic Boom
- Self leveling boom
- Hydraulic multi-connector system
- Reverse beeper
- Drive release valve
- Joystick, 8-function
- Toggle switch, hydraulic parking brake
- High volume hydraulic oil cooler
- ROPS with FOPS canopy
- 2 front head lights
- Hydrostatic direct 4WD with 4 drive motors
- Avant 760i with dual speed up to 18.6 mph, Avant 755i with single speed up to 10.5 mph
- Standard tires: Avant 760i 10-stud 400/50-15 grass or TR profile, Avant 755i 5-stud 320/60-12 TR or 26x12.00-12 grass profile
- Heated suspension seat with arm rests and seat belt
- Integrated back weight 375 lb
- Fuel tank size 10.5 gal.
- 10 gal hydraulic oil tank

Avant 700 series advantages over 600 series

- More lift capacity and handling power
- Stronger boom construction
- More oil flow for attachments, max. 21.1 gal/min
- Greater lifting height, up to 122 in
- Kohler KDI 1903 TCR turbocharged common rail diesel engine complies with Tier 4 Final emission regulations without need for diesel exhaust fluid (DEF) or active regeneration of the particulate filter (DPF)

700 series options



- A36878** Attachment control switch pack
- Controls electric functions for specific attachments
 - Consists of 3 pcs control switches, wiring and a 7-pole socket which mounts on the auxiliary hydraulics multi-connector.



- A36679** Adapter for attachment's electric connector
- converting the old electricals to fit the new multi-connector. If the loader is equipped with the electric socket integrated into the multi-connector, the attachment connector can be fitted with adapter A36679.



- A21464** Cab DLX, AC (Unit position rear)
A21510 Cab DLX, AC (Unit position roof)

- Heater and noise isolating interior
- Traffic kit
- Work light kit
- heated fabric seat with arm rests and seat belt, radio and cab air filter
- Front and rear mudguards

- A413706** Heated fabric Air suspended seat, with arm rest and seat belt -fitted only in DLX cabs



- A21517** Cab LX
- Windscreen (equipped with wiper and washer), right side window and rear window
 - Door, heater and front mudguards

- A35355** Road traffic light kit
- Headlights, turn signals, reflectors, beacon, 4-way hazards



- A21592** Cab L
- Windscreen (equipped with wiper and washer), right side window and rear window.



- MCSD500U** Cab L - soft side door
- Snap-on, zipper door to enclose cab L entry and exit.

700 series options



A33916 Work light kit: 2 front, 1 rear (LED, 700 lumen) on ROPS

A34917 Work light kit: 2 front, 1 rear (LED, 2500 lumen) on ROPS



A35732 Work light kit: 2 front, 1 rear (LED, 700 lumen) on cab LX

A35731 Work light kit: 2 front, 1 rear (LED, 2500 lumen) on cab LX



A34235 Road traffic light kit, on ROPS frame

- Headlights, turn signals, reflectors, beacon, 4-way hazards



A34002 Beacon



A36739 Beacon light bar

- Only for DLX cabs
- Gives more light than the std. beacon
- Visible from behind cab with A/C on the roof



A36652 Anti slip valve, 755i

A34529 Anti slip valve, 760i

A35719 Smooth drive (760i)

Only with boom float and self-leveling



A34015 Boom floating



PTBH-KDI Engine block heater



A418844 Auxiliary hydraulics outlet in the rear, double acting

700 series options



- A35477** Extra aux. hydr. outlet front
For customers who want to mount the tilt adapter (must be equipped with conventional type quick couplers) and a hydraulic attachment – like 4 in 1 bucket - on the machine at the same time.



- A36876** Cover plates, HD, machine with ROPS frame
A36875 Cover plates, HD, machine with ROPS & mudguards rear
A36483 Cover plates, HD, machine with LX/DLX & mudguards rear
- Heavy duty (polycarbonate)



- A420520** Mud guards, rear
- Standard with DLX cab, If adding to machine without DLX cab, rear side panels need to be changed



- A418746** Tie down bracket
A simple bracket, that makes it easier to tie down machines during transport. Fits either to the back of the machine or to side of rear frame. Can be mounted also between rear frame and trailer coupling or to rear back weight with handle, which allows the use of it even if a trailer coupling is mounted



- A417337** Trailer ball hitch 2 inch with towing pin
HH2INREC 2" Receiver hitch with tie down rings



- A36401** Rear side weight kit 176 lbs



- A49063** Rear side weight kit 400 lb

700 series options



A35957 Extra back weight with handle, 64 lbs




- MW10.278515T 27 x 8.50 - 15 TR (755/760)
- MW10.3205515G 320/55-15 HD grass (755)
- MW10.3205515T 320/55-15 HD TR (755)
- MW10.2651412G 26.5x14.00-12 (755/760)



- 65436 Weather cover for 400-700 series
- Covers the loader's interior, protects against rain, snow etc.
 - Integrated storage pouch, mounts on the ROPS frame



- 65479 Full weather cover 700 series
- Protects the entire Avant loader
 - HD storage bag



- 64973 Snow chains, pair, 26 x 12.00 -12 pic.2
- 65603 Snow chains, pair, 320/60-12 pic.2
- 65723 Snow chains, pair, 27 x 8.50-15 pic.1

Additional attachment options in back of catalog



General bucket

Avant general buckets are designed with operator in mind. Without leaving the seat the operator can see the front edge of the bucket. The sides of the general buckets flare out for complete emptying of all kinds of material. Also, there are no reinforcement plates inside the bucket to that would interfere with loading or emptying.

To further enhance the operator's visibility, there are narrow slots at the upper end of the bucket to allow the operator to see into the bucket and prevent spillage back towards the loader.

Available with straight edge and with teeth.

- All round bucket, suitable for almost every shovelling job
- Excellent visibility to the edge of the bucket
- No reinforcement plates inside the bucket – easy filling and emptying
- High breakout force
- Strong cutting edge made of high tensile, abrasion resistant wear steel



| Width | Edge | Struck Capacity | Heaped Capacity | Weight | Product no |
|---------|----------|-----------------|-----------------|--------|------------|
| 35.4 in | Straight | 5.3 cu ft | 6.7 cu ft | 137 lb | A36711 |
| 35.4 in | Teeth | 5.3 cu ft | 6.7 cu ft | 159 lb | A36716 |
| 41.3 in | Straight | 4.2 cu ft | 5.3 cu ft | 110 lb | A36702* |
| 41.3 in | Straight | 6.7 cu ft | 8.5 cu ft | 161 lb | A36710 |
| 41.3 in | Teeth | 6.7 cu ft | 8.5 cu ft | 183 lb | A36780 |
| 45.3 in | Straight | 7.4 cu ft | 9.2 cu ft | 172 lb | A36709 |
| 45.3 in | Teeth | 7.4 cu ft | 9.2 cu ft | 201 lb | A36779 |
| 51.2 in | Straight | 8.5 cu ft | 10.6 cu ft | 190 lb | A36698 |
| 51.2 in | Teeth | 8.5 cu ft | 10.6 cu ft | 216 lb | A36778 |
| 53.1 in | Straight | 8.5 cu ft | 10.6 cu ft | 199 lb | A36996 |
| 53.1 in | Teeth | 8.5 cu ft | 10.6 cu ft | 225 lb | A36997 |

*) A36702 is the general bucket for 200 series – the dimensions and weight match the lift capacity of 200 series. Wider general buckets can be used on 200 series as light material bucket.

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |





Heavy duty general bucket

Avant heavy duty general buckets are available with widths starting from 51 inches. They are made of stronger materials, are heavier and have more capacity than standard general buckets. This makes them ideal tools for harder earthmoving and material handling jobs, and the HD buckets are best suited for Avant 600 and 700 series.

There are no reinforcement plates inside the bucket which would interfere when loading and emptying, and the sides flare out to provide easy and complete emptying of all kinds of materials.

HD buckets are available with straight edge and with teeth.

- **Heavy duty bucket for more demanding earthmoving and material handling jobs**
- **Excellent visibility to the edge of the bucket**
- **No reinforcement plates inside the bucket – easy filling and emptying**
- **High breakout force**
- **Strong cutting edge made of high tensile, abrasion resistant wear steel**
- **Buckets with teeth also available**



| Width | Edge | Struck Capacity | Heaped Capacity | Weight | Product no |
|---------|----------|-----------------|-----------------|--------|------------|
| 51.2 in | Straight | 10.9 cu ft | 13.1 cu ft | 278 lb | A36713 |
| 51.2 in | Teeth | 10.9 cu ft | 13.1 cu ft | 306 lb | A36747 |
| 57.1 in | Straight | 12.4 cu ft | 14.8 cu ft | 304 lb | A36712 |
| 57.1 in | Teeth | 12.4 cu ft | 14.8 cu ft | 331 lb | A36746 |
| 63.0 in | Straight | 13.8 cu ft | 16.2 cu ft | 331 lb | A36535 |
| 63.0 in | Teeth | 13.8 cu ft | 16.2 cu ft | 364 lb | A36745 |

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Light material bucket

Light material buckets are intended for handling of snow, saw dust, manure, wood chips and other light materials.

The bottom of a light material bucket is considerably longer and the sides are higher than on a general bucket. There are no reinforcement plates inside the bucket which would interfere when loading and emptying, and the sides flare out to provide easy and complete emptying of all kinds of materials.

- **Fast and easy moving of light materials**
- **Excellent visibility to the edge of the bucket**
- **No reinforcement plates inside the bucket – easy filling and emptying**
- **High back of the bucket prevents material from falling over the rear edge and guarantees high volume**
- **Strong cutting edge made of high tensile, abrasion resistant wear steel**



| Width | Struck Capacity | Heaped Capacity | Weight | Product no |
|---------|-----------------|-----------------|--------|------------|
| 45.3 in | 12.0 cu ft | 15.2 cu ft | 276 lb | A36715 |
| 51.2 in | 13.8 cu ft | 17.5 cu ft | 298 lb | A36714 |

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



XL light material bucket

XL light material bucket is a large capacity bucket, best suited to Avant 600 and 700 series. It is intended for loading and transporting of light materials like wood chips, mulch, snow etc. There are no reinforcement plates inside the bucket which would interfere when loading and emptying, and the sides open forward in a slight angle, which guarantees easy and complete emptying of all kinds of materials and in difficult conditions also.

- **Large volume**
- **No reinforcement plates inside the bucket**
- **Robust design**
- **Intended for bigger Avant loaders**



| Width | Struck Capacity | Heaped Capacity | Weight | Product no |
|---------|-----------------|-----------------|--------|------------|
| 57.1 in | 19.8 cu ft | 25.1 cu ft | 342 lb | A36703 |
| 63.0 in | 21.5 cu ft | 27.5 cu ft | 585 lb | A36476 |
| 71.0 in | 24.7 cu ft | 31.8 cu ft | 617 lb | A36343 |

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



4 in I bucket

Efficient multi purpose bucket - can be used as a normal bucket as well as a dozer blade, leveler or a grab. The front part of the bucket opens with 2 hydraulic cylinders, located on the back side of the bucket, which enables dozing, leveling and picking of stones, tree stumps etc. Another benefit of the opening bottom is that the bucket can be emptied at a higher level by opening the bottom instead of tipping the bucket edge down.

Available with straight edge or with teeth.

- **All round tool for landscaping and groundcare**
- **A versatile bucket suitable for many different jobs at different stages on the work site**



| Edge | Width | Struck Capacity | Heaped Capacity | Weight | Product no |
|----------|---------|-----------------|-----------------|--------|------------|
| straight | 43.3 in | 5.5 cu ft | 7.8 cu ft | 335 lb | A21245 |
| straight | 50.4 in | 6.0 cu ft | 8.5 cu ft | 386 lb | A21156 |
| straight | 55.1 in | 7.4 cu ft | 9.9 cu ft | 419 lb | A21266 |
| straight | 63.0 in | 7.4 cu ft | 9.9 cu ft | 567 lb | A36906 |
| teeth | 43.3 in | 5.5 cu ft | 7.8 cu ft | 357 lb | A21249 |
| teeth | 50.4 in | 6.0 cu ft | 8.5 cu ft | 408 lb | A21184 |
| teeth | 55.1 in | 7.4 cu ft | 9.9 cu ft | 445 lb | A21269 |

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |



Compatible



Adaptable




Incompatible



High tip bucket

High tip bucket is the right choice when you need to reach higher and farther. The bucket is equipped with a hydraulic cylinder that pushes and tips the bucket over its front edge, which gives considerably more tipping height than with a normal bucket. Maximum tipping height with telescopic boom on 400, 500 and 600 series 124" and on 700 series as high as 138".

- **High tipping height**
- **Excellent for loose and light material loading**



| Width | Struck Capacity | Heaped Capacity | Weight | Product no |
|---------|-----------------|-----------------|--------|------------|
| 41.3 in | 5.3 cu ft | 6.7 cu ft | 284 lb | A2631 |
| 50.4 in | 12.4 cu ft | 14.8 cu ft | 353 lb | A2824 |

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |

Compatible
 Adaptable
 Incompatible



XL high tip bucket

The XL High tip bucket is the right choice when you need to reach higher and farther. The bucket is equipped with two hydraulic cylinders that push and tip the bucket over its front edge, giving it considerably more tipping height than with a normal bucket. The XL high tip bucket is ideal for snow removal and loading mulch, wood chips, and other light materials.

- Large volume bucket for efficient loading of light materials
- Tipping height as high as 138"



| Width | Struck Capacity | Heaped Capacity | Weight | Product no |
|---------|-----------------|-----------------|--------|------------|
| 57.1 in | 18.7 cu ft | 24.0 cu ft | 595 lb | A36841 |
| 70.9 in | 29.0 cu ft | 31.8 cu ft | 730 lb | A21273 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |





Grapple bucket

Grapple bucket combines a normal bucket and a grapple and is therefore suitable for a multitude of jobs. It can be used for transporting and loading of branches, wood chips, compost, straw, manure, construction waste etc. It can also be used as a normal bucket with the grapple in the upright position.

- **Versatile bucket for handling of loose materials**



| Width | Weight | Product no |
|---------|--------|------------|
| 35.4 in | 287 lb | A36304 |
| 41.3 in | 320 lb | A36316 |
| 51.2 in | 364 lb | A36323 |

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Demolition grapple bucket

The demolition grapple bucket with two hydraulic grapples is a strong and versatile attachment for handling of construction and demolition waste. It is also commonly used in the tree care industry to carry brush away.

- **Versatile bucket with two hydraulic grapples, for demolition, construction and tree care industry**



| Width | Weight | Product no |
|---------|--------|------------|
| 43.3 in | 400 lb | A36045 |
| 51.2 in | 435 lb | A36031 |

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |



Leveling bucket

Avant leveling buckets are built with heavy duty construction in mind. Leveling bucket has a sharp back edge which makes leveling easy when driving backward. Other features include a longer bottom, which enables the driver to see the tip of the bucket perfectly. This also makes leveling easier. The leveling buckets are strong and completely plain inside, which makes filling and emptying easier.

- **Excellent visibility to tip of bucket**
- **Sharp back edge enables exact leveling when driving backward**
- **Heavy duty design**



| Width | Struck Capacity | Heaped Capacity | Weight | Product no |
|---------|-----------------|-----------------|--------|------------|
| 57.1 in | 8.8 cu ft | 13.4 cu ft | 386 lb | A36717 |
| 63.0 in | 9.9 cu ft | 14.8 cu ft | 419 lb | A36706 |

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Pallet fork

Avant pallet fork with back frame is the right attachment for lifting and handling of different types of materials on pallets. Fork width can easily be adjusted thanks to the quick lock mechanism. The forks are made of high tensile forged steel and designed in accordance with the ISO2330 standard.

Avant is an excellent machine for load handling thanks to the precise steering and drive control. Compared with a conventional forklift truck Avant is superior when working outdoors and on terrains, be it winter or summer.

- **Excellent field of vision both to the attachment and to the environment makes working with pallet forks precise and easy**
- **Pallet fork is a useful attachment for all material handling jobs**
- **Bolt on back frame is standard**



| Model | Fork length | Max. load | Weight | Product no |
|---------|-------------|-----------|--------|------------|
| Regular | 33.5 in | 2200 lb | 198 lb | A21047 |
| Long | 43.3 in | 2200 lb | 231 lb | A21039 |
| XHD | 47.2 in | 4000 lb | 300 lb | A36589 |

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |






Pallet fork with side shift

Hydraulic fork adjustment on the pallet fork makes it possible to move the forks further apart or closer to each other easily and comfortably from the driver's seat. The forks can also be moved to the left or to the right, making it possible to shift the load to the side of the machine - closer to a wall for example. All functions can be operated from the driver's seat. Pallet fork is equipped as standard with a foldable back frame which enables handling of larger loads and protects the driver from falling objects.

- Hydraulic side shift and fork width adjustment
- Foldable back frame as standard



| Fork length | Max. load | Weight | Product no |
|-------------|-----------|--------|------------|
| 43.3 in | 2650 lb | 381 lb | A36279 |

The optional attachment control switch pack is recommended on the loader.

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Skip bucket

The skip buckets are more like skip containers, but can be transported and emptied easily with Avant. The bucket can be equipped with castor wheels as an option. The bucket can be moved and filled by hand effortlessly e.g. in horse stables, on factory floors and similar tight situations where driving with the loader is not necessary or possible. A full bucket can then be taken away and emptied with Avant.

- **Replace the waste bins on the site with the skip bucket – loading, transporting and emptying of the bucket is very easy with Avant**
- **Castor wheels available as an option (solid plastic wheels or pneumatic tires)**
- **Supports instead of wheels available as an option - they raise the rear and lower the front of the bucket by approx. 3.5 in, which makes it easier to empty e.g. a wheelbarrow into the bucket**



Options:

A418506 Castor wheels, plastic, 4 pcs (will increase bucket height by 6.5 inches)

A420800 Castor wheels, pneumatic tires, 4 pcs (will increase bucket height by 9.3 inches)

A420537 Supports, 4 pcs

| Width | Volume | Weight | Product no |
|---------|------------|--------|------------|
| 34.6 in | 22.2 cu ft | 254 lb | A36588 |
| 50.4 in | 33.5 cu ft | 320 lb | A36595 |

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Jib boom

Avant jib boom is a simple and ingenious attachment: lifting and moving heavier loads in tight situations are no longer a problem when you have this jib boom on your Avant.

The jib boom is equipped with two connecting points, one at the tip of the boom, equipped with a pin, and one 15.7 in lower. Maximum lifting height to the tip of the jib boom, with the telescopic boom of the loader extended, is about 13'.

- **Economical attachment, suitable for many different lifting jobs**
- **Connecting points on the boom increase lifting safety**



| Lift hooks | Length | Weight | Product no |
|------------|---------|--------|------------|
| 2 pcs | 47.2 in | 66 lb | A32395 |

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |

 Compatible
 Adaptable
 Incompatible




Telescoping jib boom

The hydraulically telescoping jib boom is a very efficient and versatile tool in all lifting jobs on the work site. The stepless extending and retracting boom allows lifting to places that would otherwise be very hard to reach. Compact design with telescoping cylinder inside the boom makes work safe and easy.

The jib boom is equipped with a rotating lifting hook and durable wear pads on the outer boom.

- **Excellent outreach, as much as 120" from the front wheels**
- **Max. lift height with 700 series as high as 185"**
- **Versatile lifting attachment for various load handling jobs**



| | |
|-------------------------|---------|
| Max. boom length | 74.8 in |
| Min. boom length | 51.2 in |
| Lifting height* | 185 in |
| Max load Avant 700 ser* | 880 lb |
| Max load Avant 600 ser* | 660 lb |
| Max load Avant 500 ser* | 550 lb |
| Max. outreach* | 120 in |
| Weight | 243 lb |
| Product no | A21342 |

*) Both the telescopic boom of the loader and the jib boom extended to max. outreach.

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Ball hitch on front

An easier way to move trailers, trailer mounted work platforms etc. Thanks to the perfect vision to the ball hitch it is very easy to couple a trailer by just driving the ball under the trailer and locking it in the coupling by lifting the boom of the loader. Equipped with both a ball hitch and a towing pin.

- **Easier way to couple to and move trailers etc. with Avant**
- **Best possible field of vision to the trailer enables very precise handling in tight situations**
- **Easy and fast to mount on Avant**



| | |
|--------|------------|
| Weight | Product no |
| 75 lb | A35592 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible

Hydraulic trailer hitch

Buckets, material handling

The hydraulic trailer hitch features hydraulic height adjustment of the ball hitch, which makes it easier to connect trailers in varying heights and ground conditions. The hitch is equipped with both ball and a towing pin. Attention: Requires double acting rear auxiliary hydraulics outlet on the loader.



- Equipped with ball hitch/ towing pin
- 9.8 in vertical hitch height adjustment
- Hydraulic cylinder equipped with lock valve
- Can be mounted on 400-700 series

| | |
|-------------------|--------|
| Height adjustment | 9.8 in |
| Weight | 66 lb |
| Product no | A36518 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |
| | | | | | | | | | | |

Site toolbox

This robust and versatile toolbox mounts on the attachment coupling plate and can be transported with Avant to the worksite. The flat reinforced cover can be used as a workbench. A screw vice can be also be mounted on the box.

The lid is equipped with gas springs and can be locked with a pad lock. Four lifting lugs are mounted with bolts on the sides. They can also be removed if necessary. The box is also equipped with lifting brackets for forklift.

The box keeps tools in good order and is easy to lift into the back of a truck or a safe place for the night. It can also be locked to the loader.



| | |
|------------|------------|
| Volume | 19.4 cu ft |
| Weight | 353 lb |
| Product no | A21689 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |
| | | | | | | | | | | |



Dozer blade I400

Equipped with hydraulic blade rotation, Avant dozer is the ideal tool for snow removal, earthmoving and similar jobs where the materials must be dozed away. The blade has a spring release mechanism which protects the blade and operator in the event that it hits an obstacle.

- Economical dozer blade, well suited for snow removal
- Spring release mechanism for improved safety
- Two solid skid shoes as standard - reduce blade wear and improve maneuverability
- Ice cutting edge and rubber edge available as an option



| | |
|--------------|--------|
| Blade width | 55 in |
| Angle | ±30 ° |
| Weight | 275 lb |
| Blade height | 15 in |
| Product no | A36649 |

Options:

Extensions 2 x 7 inches (can be mounted straight or in collecting position) A36651,

Ice cutting edge A32315, Ice cutting edge 7 in on extension A413823,

Rubber edge 55 in A32383, Rubber edge 7 in on extension A48870

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Dozer blade 2000

Equipped with hydraulic blade angling, Avant dozer blade is the ideal tool for snow removal, earthmoving and similar jobs where the materials must be dozed.

The blade is taller with more curvature to move material more efficiently. Hydraulic angling, spring release and skid shoes are standard equipment. So are the turnable 2 x 12.2 in extensions which can be mounted in straight or collecting position.

The floating system allows the blade to float vertically, which makes working on uneven surfaces considerably easier and more efficient. The blade can also tilt $\pm 10^\circ$. The floating system can be adjusted manually in three different positions:

- 1) Free floating – both vertically and sideways
- 2) Sideways floating $\pm 10^\circ$ only, without vertical floating
- 3) Rigid position – both vertical and sideways floating locked with bolts



Options:

A417437 Ice cutting edges, kit, for main blade and extensions

A417441 Rubber edges, kit, for main blade and extensions

A417345 Support wheels, 2 pcs

- **Two solid skid shoes which reduce blade wear and improve maneuverability**
- **Robust construction and higher blade than on I400 dozer blade for more efficient dozing**
- **Versatile dozer blade, efficient on larger areas but still compact enough for tight situations as well**
- **Turnable 2 x 12.2 in extensions as standard, can be mounted in collection position or straight**
- **Support wheels, instead of skid shoes, available as an option - keep working height more constant when working on sensitive surfaces**

| | |
|---------------|---|
| Blade width | 54.7 in main blade + 2x12.2 in bolt-on extensions |
| Slewing angle | $\pm 30^\circ$ |
| Weight | 474 lb |
| Blade height | 23.2 in |
| Product no | A36123 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Dozer blade 2500

Equipped with hydraulic blade angling, Avant dozer blade is the ideal tool for snow removal, earthmoving and similar jobs where the materials must be dozed.

The blade is taller with more curvature to move material more efficiently. Hydraulic angling, spring release and skid shoes are standard equipment. So are the turnable 2 x 12.2 in extensions which can be mounted in straight or collecting position.

The floating system allows the blade to float vertically, which makes working on uneven surfaces considerably easier and more efficient. The blade can also tilt $\pm 10^\circ$. The floating system can be adjusted manually in three different positions:

- 1) Free floating – both vertically and sideways
- 2) Sideways floating $\pm 10^\circ$ only, without vertical floating
- 3) Rigid position – both vertical and sideways floating locked with bolts



Options:

A417729 Ice cutting edges, kit, for main blade and extensions

A417672 Rubber edges, kit, for main blade and extensions

A417345 Support wheels, 2 pcs

- Two solid skid shoes which reduce blade wear and improve maneuverability
- Robust construction, with spring release mechanism designed for professional use
- Recommended for professional snow removal on larger areas
- Turnable 2 x 12.2 in extensions as standard, can be mounted in collection position or straight
- Support wheels, instead of skid shoes, available as an option - keep working height more constant when working on sensitive surfaces

| | |
|---------------|---|
| Blade width | 72.4 in main blade + 2x12.2 in bolt-on extensions |
| Slewing angle | $\pm 30^\circ$ |
| Weight | 511 lb |
| Blade height | 23.2 in |
| Product no | A36251 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Snow plow

Avant snow plow is a versatile attachment for snow removal. It consists of two independently hydraulically adjustable blades. Angle of the blades is adjusted with a switch from the driver's seat. Both blades have a spring release mechanism in the lower part of the blade to prevent any sudden stop should the blade hit an obstacle. The floating mechanism on the mounting bracket guarantees that the blade follows ground as well as possible.

The V1800 and V2400 snow plows feature:

- Vertical floating system
- Significantly more curved blade – moves snow more efficiently to the side
- Support legs with skid shoes as standard
- Curved flat cutting made of high tensile, abrasion resistant wear steel

- **Versatile snow removal tool for professional use**
- **Two independently controllable blades: can be adjusted in straight, V or Y position**
- **Advanced floating system allows working on uneven surfaces as well**

| Model | V1800 | V2400 |
|--|--------------|--------------|
| Blade width | 59.4-72.4 in | 79.5-96.5 in |
| Total width (with curved end flat edge/ ice scraper blade) | 61.8-74.8 in | 81.9-98.8 in |
| Blade turning angle | ±35 ° | ±35 ° |
| Weight | 728 lb | 860 lb |
| Blade height | 30.3 in | 30.3 in |
| Product no | A36795 | A36796 |

Requires attachment control switch pack on the loader

Option:

Ice scraper edges, kit, snow plow V1800
Ice scraper edges, kit, snow plow V2400

A36817
A36818

| Model | 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-------|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 1800 | | | | | | | | | | | |
| 2400 | | | | | | | | | | | |





V-Snow blade

Avant V-Snow Blade is a versatile attachment for snow removal. With hydraulic valve function for independent blade functions, V, Scoop, left, right and straight position.

Angling up to 30° in both directions, reversible cutting edge design with spring loaded Trip mechanism.

Blade Floats 5° and tilts 5° for ground contour.

- **Note: Blade type must be ordered with unit**



| Model | 50 | 60 |
|--------------------------------------|---------|---------|
| Height | 32.5 in | 32.5 in |
| Width | 50 in | 60 in |
| Full V | 47 in | 56 in |
| Full Scoop | 39.5 in | 48.0 in |
| Cutting Width Max Angle 30 degree | 43.5 in | 52.0 in |
| Product no | PLV5047 | PLV6056 |
| Poly blade | PB50 | PB60 |
| Metal blade | MB50 | MB60 |

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Flipper bucket

Flipper bucket is designed for clearing snow in large areas or in areas where snow must be moved long distances. Thanks to the independently controllable side wings the bucket is extremely versatile in snow clearing and can be operated in smaller areas as well without problems.

With the flipper bucket you can move a very large quantity of snow in one push. Because the wings fold out slightly forward from the sides, you can push 2-3 times the capacity of the bucket between the wings. Both wings can be operated independently. This makes the bucket easy to control also in narrow or tight areas.

- Large volume bucket, 26 cu ft
- Independently controllable side wings
- Max. working width over 118"



Option:
Ice scraper edges, kit A36504

| | |
|------------|-----------------|
| Volume | 26 cu ft |
| Width | 70.9 - 118.5 in |
| Weight | 720 lb |
| Product no | A414035 |

The optional attachment control switch pack is recommended on the loader.

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |

Compatible
 Adaptable
 Incompatible



Snow blower 1100

Avant snow blower is an efficient attachment for snow removal from sidewalks, foot paths, road and similar places where the snow must be spread out evenly. The two-stage design of the Avant heavy duty snow blower makes it a very efficient snow removal tool - also with wet and heavy snow. First the auger breaks up the snow and moves it into the fan which then throws the snow out through the discharge chute.

Discharge chute can be rotated 270°, operated from the driver's seat. Throwing height can be adjusted manually; electric throwing height adjustment available as an option. Hard snow cutters are available as an option, bolted on the sides. They facilitate cutting of hard packed snow and increase working width a bit also.



Options:

Hard snow cutters A35925

Electric throwing height adjustment A34845

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |

- **Efficient two-stage snow blower**
- **Electric discharge chute rotation as standard**
- **Hard snow cutters and electric throwing height adjustment available as an option**

| | |
|----------------|---------|
| Model | 43.3 |
| Working width | 43.3 in |
| Chute rotation | 270 ° |
| Weight | 496 lb |
| Product no | A35870 |

The optional attachment control switch pack is recommended on the loader. If the snow blower is equipped with the electric throwing height adjustment, the attachment control switch pack must be mounted.

Compatible
 Adaptable
 Incompatible



Snow blower

Avant snow blowers feature a two-stage hydraulic blower that throws snow up to 45 feet. Blower is electrically controlled, and has hydraulically operated poly-lined chute and deflector. The 25-inch high-volume shroud opening provides efficient snow removal from sidewalks, driveways, and other tight spaces.

- **Efficient two-stage snow blowers**



| Cutting Width | Cutting Height | Weight | Product no |
|---------------|----------------|--------|------------|
| 48 in | 25 in | 745 lb | PLSB48AH |
| 48 in | 25 in | 750 lb | PLSB48DH |
| 60 in | 25 in | 795 lb | PLSB60DH |

The optional attachment control switch pack A36878 is required on the loader.

| Model | 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|----------|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| PLSB48AH | | | | | | | | | | | |
| PLSB48DH | | | | | | | | | | | |
| PLSB60DH | | | | | | | | | | | |



Rotary Broom

With three working models available, 1100, 1500 and 2000. The 1500 and 2000 brooms are equipped standard with power angling by electric actuator motor. This means angling of the broom is easily and comfortably operated with a switch from the driver's seat. With a floating mechanism the brush is resting on its bristles and the whole brush axle is floating freely. The broom is equipped with supports which can be extended when the broom is not in use, so that the broom rests on the supports and the nylon brush doesn't get damaged during storage.

- Professional sweeper with manual or electric turning
- Free floating broom allows big vertical movement and guarantees excellent sweeping result
- Equipped with extendable supports for storage: nylon brush doesn't get damaged during storing



Option:
Electric turning for rotary broom 1100, product no. A36112
Wire replacement brush sections, product no. 65888

| Model | 1100 | 1500 | 2000 |
|---------------|----------|----------|----------|
| Broom width | 43.3 in | 59.0 in | 79.0 in |
| Total width | 53.9 in | 70 in | 90 in |
| Boom diameter | 21.7 in | 21.7 in | 21.7 in |
| Turning | manual | electric | |
| Turning angle | +/- 25 ° | +/- 25 ° | +/- 25 ° |
| Weight | 375 lb | 440 lb | 575 lb |
| Product no | A36067 | A35284 | A35583 |

The optional attachment control switch pack is recommended on the loader.

| Model | 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-------|--------------|--------------|--------------|--------------|------------|------------|-----------|-----------|-----------|-----------|-----------|
| 1100 | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Adaptable | Adaptable | Adaptable | Adaptable | Adaptable |
| 1500 | Incompatible | Incompatible | Incompatible | Incompatible | Adaptable | Adaptable | Adaptable | Adaptable | Adaptable | Adaptable | Adaptable |
| 2000 | Incompatible | Incompatible | Incompatible | Incompatible | Adaptable | Adaptable | Adaptable | Adaptable | Adaptable | Adaptable | Adaptable |

Compatible
 Adaptable
 Incompatible



Collecting broom I500

A collecting brush for professional property management, cities, and municipalities. The brush has a heavy duty construction, floating brush axle, automatic brush wear compensation and a specially designed water spraying system for dust binding. Enclosed construction all around the main brush provides better collection results when turning and less dust formation.



Option:
 Side brush A35698
 Water spraying system A35642

| Model | I500 |
|---------------------------|--|
| Broom width | 59.0 in |
| Total width | 70.0 in |
| Boom diameter | 21.7 in |
| Box emptying | Hydraulic (with two cylinders) |
| Box volume | 7.1 cu ft |
| Water tank volume | 40 gal |
| Weight without side brush | 935 lb (without water spraying system) |
| Weight with 1 side brush | 990 lb |
| Weight with 2 side brush | 1050 lb |

| Product no | Side brush | water spraying system |
|------------|------------|-----------------------|
| A35602 | no | no |
| A35918 | 1 brush | no |
| A35919 | 1 brush | yes |

The optional attachment control switch pack is recommended on the loader.

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |





Collecting broom 1050

Avant collecting broom 1050 is intended mainly for Avant 200 series and 400 series. Sweeping of larger yards and street cleaning is fast and efficient. Three big support wheels guarantee smooth and easy operation. Collector box emptying is hydraulic.



- **Front mounted brush rotates outwards and throws the material up and over backwards to the collector box which is closer to the machine – better balance with full collector box**
- **Thanks to the unique collecting method the box fills up completely**
- **Hydraulic emptying of collector box a standard feature**
- **Nylon brush as standard, consists of segments than can be replaced one by one**

| | |
|----------------------|-----------|
| Broom width | 41.3 in |
| Boom diameter | 19.7 in |
| Broom material | Nylon |
| Collector box volume | 6.0 cu ft |
| Product no | A33543 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Bucket broom

Bucket broom which collects waste in a large bucket shaped box. The broom gives best sweeping result when reversing, but it also works when driving forward. Forward sweeping is especially recommended when the waste is larger in dimensions, for instance construction waste, beverage cups, tree leaves, etc. The bucket broom is equipped with a floating mechanism which allows the bucket lip to rest against ground freely. To Empty the collector, first lift the broom up hydraulically, after that the collector box can be emptied by tilting it down like a normal bucket. Brush axle is equipped with a simple quick locking system for adjusting the sweeping height. Water spraying system for dust binding is also available.

- **Excellent sweeping result when driving backwards**
- **Suitable for collecting larger waste as well**
- **Large bucket shaped collector box**
- **Quick, hydraulic emptying**



| Model | 1100 | 1500 |
|--|------------|------------|
| Broom width | 43.3 in | 59.1 in |
| Total width | 53.4 in | 69.4 in |
| Box volume | 13.1 cu ft | 17.7 cu ft |
| Boom diameter | 19.7 in | 19.7 in |
| Water tank volume | 31.7 gal | 31.7 gal |
| Product no | A35945 | A35689 |
| Product no. with water spraying system | A36023 | A36024 |

Option:
 A35956 Water spraying system for Bucket broom 1100
 A35807 Water spraying system for Bucket broom 1500

| Model | 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-------|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 1100 | | | | | | | | | | | |
| 1500 | | | | | | | | | | | |





High pressure washer

The washers combine low water consumption and high water flow and pressure. High pressure water washes dust, sand and debris out of asphalt, concrete and similar surfaces and doesn't emit dust after drying. Low water consumption makes it possible to clean larger areas with a single pass.

The washer series features three models with different water tank volumes: 73 gal on model S, 147 gal on model M and 221 gal on model L. All washers are equipped with both an angling nozzle bar for street cleaning and a handheld wand with 65 foot retractable hose reel.

Max. water flow and pressure on models S and M are as high as 7 gal/min and 2900 PSI, and on the largest model L the 13 gal/min max. water flow and 3190 PSI pressure make it a very efficient cleaning machine.

Nozzle bar angling is hydraulic on models M & L, operated from the driver's seat. Model S is equipped with manual angling.



- Efficient high pressure washers, equipped with both a nozzle bar for street cleaning and with a handheld wand
- Three models: S, M and L with water tank volumes of 73 gal, 147 gal and 221 gal respectively
- Models M & L equipped with hydraulic nozzle bar angling for professional street cleaning

| Model | S | M | L |
|---------------------|-----------|-----------|------------|
| Max. water flow | 7 gal/min | 7 gal/min | 13 gal/min |
| Max. water pressure | 2900 PSI | 2900 PSI | 3190 PSI |
| Water tank volume | 73 gal | 147 gal | 221 gal |
| Working width | 59 in | 71 in | 79 in |
| Nozzles | 8 pcs | 9 pcs | 9 pcs |
| Weight | 210 lb | 503 lb | 610 lb |
| Product no | A37012 | A37013 | A37014 |

The optional attachment switch pack is recommended for washers M & L, for operating the hydraulic nozzle bar angling.

| Model | 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-------|--------------|--------------|--------------|--------------|--------------|--------------|------------|------------|------------|------------|------------|
| S | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible |
| M | Incompatible | Incompatible | Incompatible | Incompatible | Incompatible | Incompatible | Adaptable | Adaptable | Adaptable | Adaptable | Adaptable |
| L | Incompatible | Incompatible | Incompatible | Incompatible | Incompatible | Incompatible | Adaptable | Adaptable | Adaptable | Adaptable | Adaptable |



Compatible



Adaptable



Incompatible



Artificial turf attachment

The artificial turf maintenance attachment is made for professionals. It cleans, filters & returns the infill in a single pass. The fully hydraulic system powered with Avant performs the cleaning tasks efficiently, economically and with very low impact footprint in all artificial surfaces.

The regular cleaning and maintaining of the artificial surfaces reduces compaction and sustains the optimum surface conditions and playing dynamics year-around. Well maintained sport surfaces also reduce the risk of acute and chronic injuries.

- Adjustable decompaction rake and main brush
- Turbine powered dust and fine particle extraction system including 2 collection hoppers
- Adjustable and interchangeable sieving chamber with 2 large rear hoppers to collect larger debris
- Refill operating at 1.5x the ground speed to put back the cleaned infill
- Adjustable rear brush levels the infill and grooms the turf



Option:
Tilt adapter 90 degrees, to be able to access through smaller gates and corridors (requires optional second auxiliary hydraulics outlet in the front) A36505

| | |
|---------------|---------|
| Working width | 47.2 in |
| Weight | 794 lb |
| Product no | A36494 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Turf pusher

The Avant Turf Pusher is designed specifically for clearing sports turf fields. The lightweight but durable snow pusher smoothly glides over turf and field covers minimizing the displacement of infill and keeping your sports turf field operational at all times during the winter.

- **Smoothly glides over turf and field covers minimizing displacement of infill**



| | | |
|-------------|---------|---------|
| Width | 72 in. | 96 in. |
| Capacity | 3 yards | 4 yards |
| Product no. | SP06T | SP08T |

| Model | 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-------|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| SP06T | | | | | | | | | | | |
| SP08T | | | | | | | | | | | |


 Compatible
 Adaptable
 Incompatible



Sand/salt spreader

The hydraulic sand / salt spreaders are designed for fast and efficient spreading. Front mounting allows loading from ground level in the same way as with normal bucket. Powered by hydraulic motor and equipped with a mixer axle which breaks any frozen Sand/salt and prevents from clogging up. The plates in the feeding roll are spring loaded so that stones will not block or break the spreader.

- **Two models with self loading (bucket type), one with manual loading**
- **Robust design, well suited for professional use**



| Model | 900 | 900 | 1500 |
|-----------------|----------------|--------------|--------------|
| Type | manual loading | self loading | self loading |
| Spreading width | 35.4 in | 35.4 in | 59.1 in |
| Volume | 5.7 cu ft | 7.1 cu ft | 17.7 cu ft |
| Weight | 287 lb | 265 lb | 595 lb |
| Operation | Hydraulic | Hydraulic | Hydraulic |
| Product no | A2848 | A2947 | A411401 |

| Model | 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|---------|--------------|--------------|--------------|--------------|--------------|------------|------------|------------|------------|------------|------------|
| A2848 | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible |
| A2947 | Adaptable | Adaptable | Adaptable | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible |
| A411401 | Incompatible | Incompatible | Incompatible | Incompatible | Incompatible | Adaptable | Compatible | Compatible | Compatible | Compatible | Compatible |

Compatible
 Adaptable
 Incompatible



Centrifugal sand / salt spreader

Centrifugal sand or salt spreader is the right choice for winter maintenance of large areas. Spreading area can be adjusted from 6 to 20 feet which guarantees fast and efficient spreading. The spreading amount can be adjusted quickly and easily from the side of the attachment.

- **Fast spreading on large areas**
- **Manually adjustable spreading width**
- **Rear mounting also possible (700 series only)**



| | |
|--------------------------|-----------|
| Spreading width | 31-240 in |
| Volume | 8.8 cu ft |
| Max. load | 1100 lb |
| Weight | 287 lb |
| Product no., front mount | A21183 |
| Product no., rear mount* | A36523 |

*) Rear mounting possible only on 700 series. Requires also attachment mounting plate in the rear (A36552) and auxiliary hydraulics outlet in the rear.

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Towable sand / salt spreader

The towable sand / salt spreader is a very handy and economical attachment for winter maintenance of yards and walkways. Power to the spreader shaft is taken mechanically from the wheels. Wheels are equipped with a clutch which allows transporting without sand spreading. Equipped with a 2 inch trailer coupling.

Attention: The loader must be equipped with the 2 inch ball hitch A417337.

- **Economical spreader, quick to attach on the trailer coupling**
- **Mechanical power take off from the wheels – no need for rear auxiliary hydraulics**
- **Includes a durable rain cover to protect from moisture and spillage**



| | |
|-----------------|------------|
| Spreading width | 39.4 in |
| Width | 59.1 in |
| Volume | 8.1 cu ft |
| Weight | 121 lb |
| Operation | Mechanical |
| Product no | A415430 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Vacuum brush

The vacuum brush is intended mainly for collecting of tree leaves in parks, lawns, yards etc. The powerful vacuum unit sucks the waste first into the vacuum on the bottom of the collector box and then into the box, compacting everything into a tight package. The mouthpiece on the vacuum is equipped with a 47.2 in wide rotary brush which loosens also more compacted and wet leaves and waste. Brush rotation speed can be adjusted steplessly. The collector box is mounted on top of the vacuum unit. It is equipped with large transparent plastic windows so that you can easily monitor how the box is filling up. The box is emptied by opening the lid (powered by electric actuator motor) from Avant's driver seat and by lifting the boom the collected waste can be tipped into a container, skip etc.



- **Efficient leaf collector**
- **Large volume collector box allows fast collecting**
- **Equipped with Optifloat™-system, works well on uneven surfaces**
- **Easy emptying thanks to electric lid opening from Avant's driver seat**

| | |
|---------------------------|------------|
| Width without side brooms | 47.2 in |
| Collector box volume | 28.0 cu ft |
| Weight | 728 lb |
| Product no | A34714 |

The optional attachment control switch pack is recommended on the loader.

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Leguan 50 access platform

The access platform is mounted directly into Avant loaders quick attach plate. The result is an inexpensive, handy and easy to use access platform. With the help of this lift Avant's versatility is further increased on the job sites.

The Leguan 50 is mounted directly on to Avants quick attach plate like any other Avant attachment. This makes it fast and easy to mount it on and take it off.

The lift is designed according to all access platform directives and it is CE-certified. The safe working load for the lift is 440 lb which means it is allowed for operation with two men or one man with plenty of tools.

- An inexpensive access platform with 197" working height
- Safe and legal way to do building repairs, painting, light bulb changes etc.
- The maximum allowed load on the basket is 440 lb and you are able to use the lift alone
- Leguan 50 is attached to Avant which makes it easy to set it up in virtually all kinds of terrains
- The Leguan 50 access platform gives even further possibilities to use your Avant on work sites



| | |
|--------------------------------|---------|
| Max. allowed load | 440 lb |
| Max. working height | 197 in |
| Height (with lowered platform) | 74.8 in |
| Width | 51.2 in |
| Weight | 893 lb |
| Product no | A34812 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Tipping trailer

Avant tipping trailer is available in two models: with carrying capacity of 2650 lb or 4000 lb. Both are equipped with hydraulic tipping. All sides can be removed if necessary. Extra side set is available as an option for the smaller model, on the bigger model it is standard.

Attention: The loader must be equipped with the double acting rear auxiliary hydraulics outlet and the 2 inch ball hitch A417337.

- **Robust and versatile tipping trailers, well suited both for earthmoving and for lighter jobs**
- **All sides can be removed if necessary – giving a completely flat and even bed**
- **Hydraulic tipping on both models**



| Model | 1200 | 1800 |
|-------------|---------------|--------------|
| Max. Load | 2650 lb | 4000 lb |
| Width | 44.3 in | 53.1 in |
| Length | 67.3 in | 88.2 in |
| Tire size | 23 x 8.5 - 12 | 26 x 12 - 12 |
| Side height | 11.0 in | 22.0 in |
| Product no | A2949 | A21200 |

Option: Extra side set (A45193) for 1200 model

| Model | 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-------|--------------|--------------|--------------|------------|------------|------------|------------|------------|------------|------------|------------|
| 1100 | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible |
| 1800 | Incompatible | Incompatible | Incompatible | Adaptable | Adaptable | Adaptable | Compatible | Compatible | Compatible | Compatible | Compatible |



Compatible



Adaptable



Incompatible



Trailer / timber trailer

Avant trailer with manual tipping is useful when transporting garden waste, topsoil, mulch etc. In addition, all sides can be removed if necessary, which makes the trailer an excellent timber transporting vehicle. Big wheels guarantee it will travel on wet ground as well. Equipped with a rotating trailer coupling. Both single and tandem axle versions available

Attention: The loader must be equipped with the 2 inch ball hitch A417337.

- **Versatile – can be used both as a normal and timber trailer**
- **Both single and tandem axle versions available**
- **Equipped with rotating trailer coupling**
- **Manual tipping**



| Model | Single axle | Double axle |
|--------------|----------------|-------------|
| Own weight | 220 lb | 285 lb |
| Total weight | 1100 lb | 1850 lb |
| Floor size | 25.6 x 68.9 in | |
| Total width | 47.2 in | |
| Product no | A21110 | A21111 |

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |





Lawn mower 1200

The mower 1200 is a robust and efficient mower deck. It is equipped with the Optifloat™ floating system, developed by Avant, which provides optimal cutting on uneven terrain. The mower is also equipped with a safety valve which stops the blades when the mower is lifted off the ground. The deck is made of stamped steel. This makes mowing more efficient and the grass clippings don't get stuck on the deck so easily.

The mower is mulching type as standard. Side discharge kit is available as an option.

- **Optifloat™ floating system provides easy operation and good mowing result on uneven lawns**
- **Safety valve stops the blades when the mower is lifted off the ground**
- **Thanks to stamped steel deck mowing is more efficient and the deck stays cleaner**



| | |
|----------------|--------------|
| Cutting width | 47.2 in |
| Blades | 2 pcs |
| Cutting height | 1.0 - 4.0 in |
| Weight | 375 lb |
| Product no | A35965 |

Option: Side discharge kit A36013

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |

Compatible
 Adaptable
 Incompatible



Lawn mower 1500

Avant's biggest lawn mower is intended for lawn mowing of larger areas. The mower can be adjusted to right type of mowing for different circumstances.

Powerful mower allows a higher drive speed and perfect cut even in challenging conditions.

Optifloat™ system ensures that the cutting is easy and that the cutting deck follows the ground contours also on uneven terrains. The floating system is also equipped with a safety valve, which stops the blades when the mower is lifted off the ground.

- **Optifloat™ floating system provides easy operation and good mowing result on uneven lawns**
- **More cutting power for challenging mowing conditions**
- **Side discharge as standard, mulching kit available as an option**
- **Rounded edge design reduces damage to trees, buildings, etc. in case of contact**



| | |
|----------------|--------------|
| Cutting width | 59.0 in |
| Blades | 3 pcs |
| Cutting height | 1.0 - 4.0 in |
| Height | 17.7 in |
| Weight | 485 lb |
| Product no | A34528 |

Optional extras: Mulching kit (complete assembly kit) A34530

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Collecting lawn mower 1200

With the Avont collecting mower 1200 you can easily mow and collect the clippings. Thanks to its excellent suction power collecting leaves from the lawns is also possible.

The mulching blades of the mower crush the grass clippings, leaves etc. into a very fine material which then moves to the collector and forms a tight and compact package. The cutting waste is ideal material for composting. Collector capacity is as big as 55.5 gal. Emptying of the collector is very easy: lift the mower up from the ground with Avont's boom and then tilt the mower downward so much that the grass waste pushes the lid open and the waste comes out.

- **Powerful mower with a collector unit**
- **Can also be used for collecting tree leaves on lawns**
- **Vacuum fan can be turned off and the unit can be used as a mulching mower only**
- **Optifloat™ floating system provides easy operation and good mowing result on uneven lawns**

| | |
|----------------------|--------------|
| Cutting width | 47.2 in |
| Blades | 2 pcs |
| Cutting height | 1.0 - 4.0 in |
| Collector box volume | 7.4 cu ft |
| Product no | A35973 |



| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Collecting lawn mower I 500

Collecting mower designed for professional use with 59" cutting width and 28 cu ft collector box. The high suction power makes it also possible to collect tree leaves on lawns. The blades cut the grass, tree leaves etc. to a fine mulch which packs tightly into the collector box.

Collector box volume is designed to be large enough for professional use in larger areas. The box is emptied from Avanti's driver seat with an electric switch and with the help of Avanti's boom the collector can be emptied into a container, skip etc.

- Equipped with Optifloat™ system
- More cutting power for challenging mowing conditions
- Vacuum fan can be turned off and the unit can be used as a mulching mower only
- Rounded edge design reduces damage to trees, buildings, etc. in case of contact



| | |
|----------------------|--------------|
| Cutting width | 59.0 in |
| Height | 43.3 in |
| Blades | 3 pcs |
| Cutting height | 1.0 - 4.0 in |
| Collector box volume | 28.0 cu ft |
| Product no | A34495 |

The optional attachment control switch pack is recommended on the loader.

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |





Flail mower

Flail mower is a drum-type cutter, intended for cutting of long grass, scrub, bush and similar vegetation. It will cut up to 0.8" thick tree branches with ease.

Flail mower is the optimal cutting device for places where you need a lot of cutting power and a rougher cut will do. The most common applications for flail mower are places with taller vegetation like meadows, road sides, fields etc.



Optional flail types:
 A419931 Y-flails, pair, 16 Pcs/47.2 in mower, 20 Pcs/59 in mower
 A420305 L-flails, pair, 16 Pcs/47.2 in mower, 20 Pcs/59 in mower

- **Unique cutting deck design - improves cutting result, requiring less power from the engine and hydraulics**
- **Flails are mounted in spiral configuration on the shaft which makes cutting more efficient**
- **Direct drive: hydraulic motor mounted directly on the shaft**
- **Floating system allows free vertical movement, and the floating can be set so that the mower can tilt forward and backward**
- **Bigger roller in the rear – better stability and less resistance when mowing**
- **Both models equipped as standard with hammer type flails – Y and L type flails are available as an option**

| | | |
|--------------------------|------------------|------------------|
| Cutting width | 47.2 in | 59 in |
| Total width | 62.2 in | 74 in |
| Cutting height | 1 - 4 in | |
| Standard flails type/pcs | hammer 16 pcs | hammer 20 pcs |
| Weight | 530 lb | 595 lb |
| Product no | A36730 | A36015 |

| Model | 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-------|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 1200 | | | | | | | | | | | |
| 1500 | | | | | | | | | | | |

Compatible
 Adaptable
 Incompatible



Cutting bar

An uncomplicated cutting bar for mowing of hay, grass and trimming of bushes and hedges. Thanks to the side mounting and angle adjustment below ground level, mowing of slopes is also possible. Guide plates support the cutting bar when mowing on uneven terrain.

Spring loaded release mechanism allows the bar to move backwards if it hits an obstacle. Cutting angle can be adjusted manually with the hand winch. Electric cutting angle adjustment is available as an option.



- **Robust and economical long hay cutter and hedge trimmer**
- **Cutting angle adjustment below ground level - mowing of slopes also possible**
- **Spring loaded release mechanism for increased safety - cutting bar gives in when hitting an obstacle**
- **Electric cutting angle adjustment available as an option**

| | |
|------------------|---------|
| Cutting width | 57.1 in |
| Transport width | 100 in |
| Transport height | 70.0 in |
| Weight | 220 lb |
| Product no | A35676 |

Optional extras: Electric cutting angle adjustment A35975

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Fingerbar mower with hydraulic boom

Versatile attachment for hedge cutting, long hay mowing etc. The hydraulically operated boom gives excellent outreach, and it can be extended to both sides of the machine. Strong fingerbar type cutting head can cut max. 1" branches.

- Versatile attachment for hedge cutting and hay mowing
- Over 10 ft of outreach thanks to hydraulic booms
- Equipped with three axis progressive cable controls



| | |
|---------------|---------|
| Outreach | 138 in |
| Cutting width | 47.2 in |
| Weight | 495 lb |
| Product no | A411395 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Flail mower with hydraulic boom

The flail mower with hydraulic boom can reach to places where it is not possible to drive with the machine. This makes mowing road banks, ditches, waterfronts and other hard-to-reach areas safe and easy. The mower is equipped with proportional controls and joystick for smooth and exact movements of the boom and the mower deck.

It is recommended that the Avant is equipped with a cab (L, LX or DLX) in order to protect the driver against flying debris. When mounted on Avant 600 series, the extra side weights (A49063) are also recommended for better stability.

- **Excellent visibility to the whole working area – the operator can look into the driving direction when mowing**
- **11 ft outreach**
- **Smooth and easy proportional controls with joystick**



| | |
|---------------|---------|
| Outreach | 138 in |
| Cutting width | 39.4 in |
| Weight | 770 lb |
| Product no | A410727 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |





Edge trimmer

Avante edge trimmer is the perfect attachment for trimming the edges of lawns, hedges, flower beds etc. It consists of a hydraulically operated trimmer mounted next to a cutting disc.

Cutting disc cuts lawn precisely where you want and hydraulic trimmer breaks up any soil or lawn that is left to the side of the cutting disc. Edge trimmer leaves a good looking finish to any garden thanks to its adjustable cutting depth and precise control.

The edge trimmer is equipped with manually extendable arm and can be turned in three different positions: to the right side or to the left side, or to the front for transport. Support wheel is available as an option.



Option: Support wheel A36699

- Cuts the lawn edge accurately, leaving a finished look on lawns, flower beds, driveways, walkways etc.
- Hydraulic trimmer mills the soil efficiently
- Equipped with manually extendable arm
- Can be turned manually in three positions: to the left or to the right side, and to center transport position
- Support wheel available as an option

| | |
|--------------------------------|-----------|
| Cutting depth | max. 6 in |
| Cutting disc diameter | 18.1 in |
| Cultivating width | 6.1 in |
| Height | 22.8 in |
| Weight | 176 lb |
| Min. width in working position | 42.5 in |
| Product no | A36621 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Weed brush

Weed brush is an efficient tool for removal of weeds on all kinds of paved areas etc. It is equipped with a steel brush which can be extended manually and turned in three different positions: to the front, to the right side or to the left side. The weed brush is equipped with a support wheel as standard. It can be lifted and locked up to transport position if needed.

- **Efficient weed removal with rotating steel brush**
- **Equipped with manually extendable arm**
- **Can be turned manually in three positions: to the left or to the right side, and to center transport position**
- **Support wheel as standard**



| | |
|--------------------------|---------|
| Brush diameter | 23.6 in |
| Bristle material | steel |
| Height | 20.9 in |
| Length/Width (retracted) | 43.3 in |
| Weight | 187 lb |
| Product no | A36594 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |





Rotary hoe

Avant rotary hoe is the basic attachment for soil cultivating, seed bed finishing and rotovating. Adjustable cultivating depth up to 6". Can be equipped with a field roller which compacts the ground after cultivating.

- **An inexpensive and robust rotary hoe**



| | | |
|---------------|--------------|---------|
| Model | 1100 | 1300 |
| Working width | 43.3 in | 51.2 in |
| Working depth | 2.0 - 6.0 in | |
| Weight | 350 lb | 395 lb |
| Product no | A2808 | A21163 |

Optional extras:

- Field roller for 1000 model A2972
- Field roller for 1300 model A21164

| Model | 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-------|--------------|------------|------------|--------------|--------------|------------|--------------|--------------|--------------|--------------|--------------|
| 1000 | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Incompatible | Incompatible | Incompatible | Incompatible | Incompatible |
| 1300 | Incompatible | Compatible | Compatible | Incompatible | Incompatible | Adaptable | Compatible | Compatible | Compatible | Compatible | Compatible |



Compatible



Adaptable



Incompatible



Stone burier

A hydraulic stone burier for preparation of lawn beds. The stone burier mills the soil, buries stones and other objects up to 6.3" deep in a single pass, making a milled and tamped topsoil. Working depth is steplessly adjustable with the rear field roller. With the optional seeding unit you are able to make a ready lawn surface on one pass.

Stone buriers are most commonly used when the topsoil needs to be milled thoroughly. The soil is milled more thoroughly and deeper than with a rotary harrow.

- **Efficient stone burier**
- **Top grade finish with just one pass**
- **Can be equipped with seeding unit**



Optional extras:

- Seeding unit for 1130 model (A21011)
- Seeding unit for 1300 model (A21238)
- Seeding unit for 1500 model (A410304)

| Model | 1130 | 1300 | 1500 |
|--------------------------|------------|---------|------------|
| Working width | 44.5 in | 51.2 in | 59.1 in |
| Roller width | 52.0 in | 59.1 in | 66.9 in |
| Working depth | 0 - 5.9 in | | 0 - 6.3 in |
| Weight | 480 lb | 550 lb | 640 lb |
| Weight with seeding unit | 550 lb | 640 lb | 730 lb |
| Product no | A21010 | A21237 | A410303 |

| Model | 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|
| 1130 | Compatible | Compatible | Compatible | Incompatible |
| 1300 | Incompatible | Incompatible | Incompatible | Adaptable | Adaptable | Adaptable | Incompatible | Incompatible | Incompatible | Adaptable | Adaptable |
| 1500 | Incompatible | Incompatible | Incompatible | Incompatible | Incompatible | Incompatible | Adaptable | Incompatible | Incompatible | Incompatible | Incompatible |



Compatible



Adaptable



Incompatible



Rotary harrow

Avant rotary harrow is an excellent leveler for lawn beds, yards, gardens etc. – for places where the ground needs to be perfectly leveled. It harrows only the topsoil and gives a very nice finish for sowing. Required output is lower than that of the stone burier which allows also a higher working speed. Working depth is adjusted with the rear field roller which levels the seeding bed during operation. With the optional seeding unit you are able to make a ready lawn surface on one pass.

Rotary harrows are most commonly used for lighter topsoil leveling. The soil is normally not milled as deep or as thoroughly as with a stone burier.

- Professional, efficient rotary harrow for topsoil leveling
- Top grade finish with just one pass
- Can be equipped with seeding unit
- Requires less power than stone burier



Optional extras:

- Seeding unit for 1350 model (A21085)
- Seeding unit for 1500 model (A21193)
- Seeding unit for 1700 model (A415800)

| | | | | |
|--------------------------|------------|---------|---------|---------|
| Model | 1200 | 1350 | 1500 | 1700 |
| Working width | 41.3 in | 48.0 in | 55.1 in | 61.0 in |
| Roller width | 47.2 in | 53.1 in | 59.1 in | 67.0 in |
| Working depth | 0 - 6.3 in | | | |
| Weight | 397 lb | 485 lb | 550 lb | 640 lb |
| Weight with seeding unit | - | 575 lb | 640 lb | 730 lb |
| Product no | A21067 | A21077 | A21185 | A21431 |

| Model | 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-------|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 1200 | | | | | | | | | | | |
| 1350 | | | | | | | | | | | |
| 1500 | | | | | | | | | | | |
| 1700 | | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Leveler

A simple and inexpensive but incredibly useful and efficient attachment for leveling and planing of larger areas. With Avant leveler you can easily and quickly level sand, mulch etc. The leveler is most commonly used in:

- Preliminary lawn bed leveling
- Yard sand leveling
- Driveway leveling

The leveler can also be used for lifting job site materials like sod rolls, tools etc.

- **Economical attachment for leveling gravel and other soil materials**
- **Eliminates almost all manual shoveling at job sites**



| Width | Weight | Product no |
|---------|--------|------------|
| 47.2 in | 187 lb | A32411 |
| 59.1 in | 210 lb | A33537 |

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |






Front rake

Front rake is an economical attachment for leveling of sand and gravel driveways, anywhere you want to have a nice looking finish. The spring loaded tines rake and level the ground efficiently.

The rake can also be used for loosening and leveling of uneven soils.

- **Economical leveler for sand gravel driveways**
- **Works on soils as well**
- **Can be mounted on all Avant models**



| | |
|--------------|---------|
| Width | 78.7 in |
| Tine height | 9.6 in |
| Total height | 22.1 in |
| Weight | 77 lb |
| Product no | A36968 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Ripper

The ripper is a practically irreplaceable tool in ground works. With the ripper it is easy and effortless to remove roots as well as rocks even from hard packed ground. The replaceable hard metal teeth provide a long lifespan for the attachment.

The ripper is operated by pressing the three blades into the ground next to the object you wish to remove. When the teeth have sunk into the ground, tilt the ripper inwards and then lift the boom upwards which will bring the object on top of the ground.

- **A tool for removing of rocks, tree stumps, roots etc. from the ground**
- **Eliminates a huge amount of manual work**



| | |
|---------------|-----------------|
| Width | 20.0 in |
| Working depth | approx. 12.0 in |
| Weight | 110 lb |
| Product no | A44412 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Screening bucket

The Avant screening bucket is a fast and efficient compact system for screening and blending soils, aggregates and compost. The durable and flexible star-shaped plastic Poly Star rollers screen without shredding the vegetation or crushing the aggregates into the finished screened product.

The unique design fitted with sealed bearings, self tensioning carbon belt driveline and flexible Poly Stars enables for a large screening area to create a low maintenance, fast and efficient screening system.

- Separates stone/soil/vegetation
- Screens without crushing or shredding
- Suitable for different types of soil

| | |
|----------------|----------------|
| Width | 55.5 in |
| Bucket volume | 9.1 cu ft |
| Screening area | 47.2 x 16.9 in |
| Weight | 860 lb |
| Product no | A36503 |



| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Stump grinder

The Avant Stump Grinders are the benchmark for rugged design, minimal maintenance, and cutting speed. Stump grinding can be a profit center for your tree service business, landscape company, farm operation, or rental yard using the Avant you already own.

The Avant Stumper 220 and Stumper 240 are mid-size grinders that chew up from 6" to 8" of stump per pass, while offering lighter weight and high flow hydraulic power. These stumper grinders cut on the face and edge of the wheel, so you get several inches of cut per-pass. Quick attach, no electrical connections and minimal maintenance -- just drive up and grind.

- **Up to 24 inch cutting diameter with a 6 inch to 8 inch cutting depth**
- **Grind stumps in a matter of minutes**
- **Attaches quickly, minimal maintenance--just drive up and grind.**



| Model | Stumper 220 | Stumper 240 |
|------------------|----------------|----------------|
| Cutting Diameter | 22 in | 24 in |
| Cutting Depth | 6 in. per pass | 8 in. per pass |
| Weight | 375 lb | 475 lb |
| Product no. | ST220AV | ST240AV |

| Model | 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|---------|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| ST220AV | | | | | | | | | | | |
| ST240AV | | | | | | | | | | | |





Stump buster

A safer and faster way of removing tree stumps!

The stump buster is an efficient, easy and safe way for removing tree stumps. The three blade drill head has slow speed and high torque, which means it can be used within confined spaces and pedestrian areas safely.

The stump buster drills either a 10" or a 14" diameter hole into the tree stump, shaving off the wood as it turns.

The drive unit is equipped with a hydraulic motor and planetary gearbox which provides high torque and efficient cutting. The stump buster comes with a 20" long drive shaft and replaceable teeth blades. Teeth blades are made from very hard material which will give prolonged life in stoney ground conditions.



- **Safe way for removing of tree stumps**
- **Uncomplicated design, easy to operate**
- **Bolt-on, replaceable blades**

| | |
|------------------------|------------|
| Model | XHD92 |
| Max. torque | 4330 lb/ft |
| Drive shaft length | 20.0 in |
| Weight | 660 lb |
| Drive unit product no. | A33571 |

Drills:
 Drill 10", A36763
 Drill 14", A36764

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Stone grab

The mechanical stone grab is easy to mount on the Avant jib boom. Thanks to the powerful gripping force it can handle concrete components, curb stones, natural stones, tombstones etc.

The stone grab is equipped with:

- Lifting eye for attaching to Avant jib boom hook
 - Automatic load release
 - Changeable rubber covered steel grabs
 - Spring loaded bolt for quick and easy opening width adjustment
- With the Avant jib boom (A32395) and telescopic boom extended the maximum outreach is 83", measured from the front wheel. When using the telescoping Avant jib boom A21342 maximum outreach is as high as 120".

ATTENTION! Avant jib boom (A32395 or A21342) is required for lifting of the stone grab.

- **Scissor type lifting device for:**
 - Curb stones
 - Concrete components
 - Tombstones
 - Natural stones
- **Scissor mechanism is completely mechanical, doesn't require hydraulics**



| | |
|------------------|---------------|
| Gripping width | 2.0 - 19.0 in |
| Jaw height | 6.7 in |
| Jaw length | 16.5 in |
| Lifting capacity | 1985 lb |
| Weight | 121 lb |
| Product no | A21179 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |




Stone installation clamp

With the hydraulic installation clamp you can lay paving stones quickly and efficiently. The installation clamp takes a whole layer of paving stones directly from a pallet, which can then be lifted on to the area to be paved.

The hydraulic installation clamp is equipped with:

- adjustable side grippers for the exact shaping of the installation pattern.
- hydraulic rotation
- ADV pushing off device. The ADV presses the blocks into the laying course automatically once the clamp is opened – this way the cocking of the blocks can be avoided and a lot of time is saved, because one doesn't have to reposition the blocks by hand. Avant jib boom (A32395) is also required, for lifting and handling of the clamp.



- **For professional and fast stone laying**
- **Minimizes hand labour and intensive manual lifting**

| | |
|------------------|----------------|
| Gripping width | 22.6 - 49.0 in |
| Total width | 39.0 - 58.3 in |
| Lifting capacity | 880 lb |
| Weight | 507 lb |
| Product no | A21180 |

Requires attachment control switch pack on the loader

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible




Grabbing tool

Grabbing tool is mainly intended for lifting and handling of round objects. It is especially suited for lifting of barrels, plant and tree pots. Grabbing force can be adjusted, which means all kinds of objects can be handled without damaging them.

Grabbing tool is equipped with two smaller, rubber padded grabs which allow handling of smaller and more fragile objects as well. When the grab is opened completely it can take larger objects like barrels, bigger plant pots etc.

- **Easiest way to lift and transport plants, trees, barrels etc. without damaging them**
- **Excellent tool for nurseries and landscapers**
- **With the optional tilt adapter it is also possible to rotate the objects max. 90 degrees**



| | |
|--------------------|---------|
| Min. grab diameter | 10.0 in |
| Max. grab diameter | 47.0 in |
| Max. load | 1430 lb |
| Weight | 210 lb |
| Product no | A34290 |

Option:
Tilt adapter 90 degrees A36505
(requires second auxiliary hydraulics outlet in the front)

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |







Backhoe 170

Avant backhoe 170 is a compact digging unit, intended mainly for Avant 200 series. The main focus of the design is user friendliness and straight forward construction. Backhoe 170 is a small backhoe, which is at its best in tight situations where space is limited. Boom movements are smooth and precise, which makes operation easier for less experienced users. To facilitate digging, the frame of the backhoe is as low as possible, which gives unrestricted visibility to the work area.

- **Strong and compact backhoe**
- **Easy to connect and disconnect to Avant**
- **Smooth movements with precise control valve, easy to operate**



| | |
|--------------------|------------------|
| Max. Digging depth | 66.9 in |
| Standard bucket | 9.8 in / A415232 |
| Weight | 397 lb |
| Product no | A36848 |



Optional extras:
 Bucket 15.7 in A415230
 Bucket 29.5 in A35564

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Backhoe 210


Avant backhoe 210's main focus in design is user friendliness and straight forward construction.

Boom movement speeds are steplessly adjustable, which makes operation easier, especially for inexperienced users. To facilitate digging, the frame of the backhoe is as low as possible, which gives unrestricted visibility to the work area.

- **A powerful, strong and compact backhoe**
- **Easy to connect and disconnect to Avant**
- **Smooth movements with precise control valve, easy to operate**
- **Uncomplicated and economical backhoe**



| | |
|--------------------|-------------------|
| Max. Digging depth | 82.7 in |
| Standard bucket | 15.7 in / A415230 |
| Weight | 419 lb |
| Product no | A33747 |



Optional extras:

Bucket 9.8 in A415232

Bucket 29.5 in A35564

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Backhoe 260

The Backhoe 260 has many advanced features: boom swing happens with two hydraulic cylinders, that gives more exact boom movements when swinging and requires less service. Swing angle is 170 degrees.


Backhoe 260 is equipped with hydraulic outriggers as standard. The operator can easily adjust the outriggers with the lever on the backhoe control valve. This allows quick and easy set up on uneven terrains.

Changing of bucket is easy thanks to the quick attach mechanism. Mounting the backhoe on Avant is fast, and easy.

- **Powerful and professional backhoe with good outreach**
- **Hydraulic outriggers**
- **Bucket quick attach system S30-150**
- **170 degree boom swing angle with consistent speed**
- **Dozer blade on front frame**
- **Several bucket options**
- **Bucket sideways tilt adapter available as an option**

Optional extras:

- Bucket 9.8 in A414301
- Bucket 29.5 in A35230
- Bucket 39.4 in A35383
- Quick attach adapter S30-150 with sideways tilt A35249



| | |
|--------------------|-------------------|
| Max. Digging depth | 102 in |
| Width | 51.2 in |
| Boom swing angle | 170 ° |
| Standard bucket | 15.7 in / A414304 |
| Weight | 925 lb |
| Product no | A35248 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Mini digger

Avant mini digger is an efficient solution for small digging operations where maximum digging depth of 47.2 in or 59.1 in is enough. It mounts directly on the quick attach plate of the loader and is operated with the auxiliary hydraulics control lever. Dumping to the side happens by turning the steering wheel of the Avant.

Mini digger 150 is equipped with the S30 bucket quick attach system (same as on backhoe 260), which makes changing of bucket fast and easy - and the bucket can also be mounted pointing forward if necessary. Bucket tilt adapter for mini digger 150 is available as an option.



- **Efficient and economical solution for smaller digging jobs**
- **Very fast to mount on Avant**
- **Simple and light to transport from one job site to another**
- **High unloading height**
- **Bucket tilt adapter available as an option for mini digger 150**

| Model | 120 | 150 |
|---------------------|---------|---------|
| Max. digging depth | 47.2 in | 59.1 in |
| Standard bucket | 9.8 in | - |
| Weight | 155 lb | 187 lb |
| Product no | A36822 | A36856 |
| Buckets available | | |
| 9.8 lb | A415232 | A414301 |
| 15.7 in | A415230 | A414304 |
| 29.5 in | A35564 | A35230 |
| 39.4 in | - | A35383 |
| Bucket tilt adapter | - | A35320 |

| Model | 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-------|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 120 | | | | | | | | | | | |
| 150 | | | | | | | | | | | |



Compatible



Adaptable




Incompatible



Trencher

The Avant trencher is a compact yet powerful tool. It features an adjustable depth control foot which ensures the operator digs at a set depth (up to 36 in) at all times and efficient spoil removal for effective compaction back into the trench. Three different chains types and three chain widths are available for trenching in different ground conditions from general earth, to rocky ground, and even frozen ground.

The Avant DG90 Trenchers are ideal for laying pipe for irrigation, underground power and communications, road repairs and general construction.



| Model | Digging Width | Chain Type | Motor Disp. |
|---------|---------------|-------------|-------------|
| DG904EA | 4 in | Earth | 6.2 cu in |
| DG904CA | 4 in | Combo | 6.2 cu in |
| DG904SA | 4 in | Shark Tooth | 6.2 cu in |
| DG906EA | 6 in | Earth | 6.2 cu in |
| DG906CA | 6 in | Combo | 6.2 cu in |
| DG906SA | 6 in | Shark Tooth | 6.2 cu in |
| DG908EA | 8 in | Earth | 6.2 cu in |
| DG908CA | 8 in | Combo | 6.2 cu in |
| DG908SA | 8 in | Shark Tooth | 6.2 cu in |
| DG904ED | 4 in | Earth | 8.0 cu in |
| DG904CD | 4 in | Combo | 8.0 cu in |
| DG904SD | 4 in | Shark Tooth | 8.0 cu in |
| DG906ED | 6 in | Earth | 8.0 cu in |
| DG906CD | 6 in | Combo | 8.0 cu in |
| DG906SD | 6 in | Shark Tooth | 8.0 cu in |
| DG908ED | 8 in | Earth | 8.0 cu in |
| DG908CD | 8 in | Combo | 8.0 cu in |
| DG908SD | 8 in | Shark Tooth | 8.0 cu in |

| Model | 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|---------|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| DG90**A | | | | | | | | | | | |
| DG90**D | | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Auger

Avant's drilling drives are the ultimate in performance, quality and cost effectiveness. Using only the highest grade materials and strictest quality control, Avant offers the highest quality range of auger drives on the market today.

Fitted with Eaton bell motors and input housing, the innovative design allows the gearbox to go down the hole to maximize drilling depth without extensions, eliminating downtime and minimizes maintenance, optimizing your returns.



| Model | Auger | Torque | Product no |
|--------------|---------|------------|------------|
| Direct drive | 6-12 in | 1000 lb/ft | A37092 |
| DG1DSS | 6-24 in | 1467 lb/ft | DG1DSS |
| DG3DSS | 6-36 in | 2829 lb/ft | DG3DSS |

| Product no. | Auger Size | Drill Bit |
|-------------|------------|-----------|
| DG06EA | 6 in | Earth |
| DG08EA | 8 in | Earth |
| DG09EA | 9 in | Earth |
| DG10EA | 10 in | Earth |
| DG12EA | 12 in | Earth |
| DG14EA | 14 in | Earth |
| DG16EA | 16 in | Earth |
| DG18EA | 18 in | Earth |
| DG20EA | 20 in | Earth |
| DG24EA | 24 in | Earth |
| DG30EA | 30 in | Earth |
| DG36EA | 36 in | Earth |

| Product no. | Auger Size | Drill Bit |
|-------------|------------|-------------------|
| DG06HD | 6 in | Earth w/ Tungsten |
| DG08HD | 8 in | Earth w/ Tungsten |
| DG09HD | 9 in | Earth w/ Tungsten |
| DG10HD | 10 in | Earth w/ Tungsten |
| DG12HD | 12 in | Earth w/ Tungsten |
| DG14HD | 14 in | Earth w/ Tungsten |
| DG16HD | 16 in | Earth w/ Tungsten |
| DG18HD | 18 in | Earth w/ Tungsten |
| DG20HD | 20 in | Earth w/ Tungsten |
| DG24HD | 24 in | Earth w/ Tungsten |
| DG30HD | 30 in | Earth w/ Tungsten |
| DG36HD | 36 in | Earth w/ Tungsten |

| Product no. | Auger Size | Drill Bit |
|-------------|------------|-----------|
| DG06RT | 6 in | Rock |
| DG08RT | 8 in | Rock |
| DG09RT | 9 in | Rock |
| DG10RT | 10 in | Rock |
| DG12RT | 12 in | Rock |
| DG14RT | 14 in | Rock |
| DG16RT | 16 in | Rock |
| DG18RT | 18 in | Rock |
| DG20RT | 20 in | Rock |
| DG24RT | 24 in | Rock |
| DGEXT2 | 24 in | Extension |
| DGEXT3 | 36 in | Extension |

| Model | 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|--------------|--------------|--------------|--------------|------------|------------|------------|------------|------------|------------|--------------|--------------|
| Direct drive | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible |
| DG1DSS | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Compatible | Incompatible | Incompatible |
| DG3DSS | Incompatible | Incompatible | Incompatible | Adaptable | Adaptable |



Hydraulic breaker

Avant breakers are specially designed for use with Avant loaders. From three different models you can find suitable for all 400, 500, 600 and 700 series models.

Avant loader with breaker is a very efficient tool in demolition and refurbishing operations: do the demolition with Avant and breaker, take the debris away with Avant and bucket – very fast and effective.

Another benefit of this combination is its compact dimensions:

Avant breakers are the fastest, easiest and most efficient breakers for Avant loaders. All hoses, couplings and quick attach brackets are included in the package. In addition, breakers are pre-adjusted at the factory to suit Avant loaders.



- **Top quality sound isolated**
Avant breakers are quiet and powerful
- **Breakers are pre-adjusted at the factory to suit Avant loaders. There is a breaker for each Avant model**
- **All hoses and adapter plates are included in the packaging so the combination is all ready for work**
- **Multiple tools available for example: chisel, wedge, moil point and blunt.**

| Model | Impact rate (frequency) | Weight | Product no |
|-------|-------------------------|--------|------------|
| B105 | 600-3200 bpm | 231 lb | A36423 |
| B155 | 800-3000 bpm | 342 lb | A36424 |
| B230 | 700-2600 bpm | 507 lb | A36425 |

| Model | 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-------|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| B105 | | | | | | | | | | | |
| B155 | | | | | | | | | | | |
| B230 | | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Cutter crusher C290

Avant cutter crusher is intended for professional demolition work. With the cutter crusher you are able to crush concrete, bricks and cut metal rebars into smaller pieces with the same tool. The cutter crusher is equipped with free rotation to allow self-positioning during working. The closing force of the jaws is controlled by a booster system which automatically increases the power when it meets strong resistance. Different types of interchangeable tips are available to improve the penetration and grip of the machine.

- **Efficient, noise and vibration free crushing**
- **Equipped with free rotation to allow self-positioning during working**



| | |
|--------------------|------------------|
| Jaw opening | 15.7 in |
| Max cutting force | 287,000 lb |
| Max crushing force | 97,000 lb |
| Rotation | 360° (endlessly) |
| Weight | 640 lb |
| Product no | A36492 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |





Concrete mixing bucket

Concrete mixing bucket is a handy tool when you need to make concrete without electricity or when you need to transport or lift the concrete to a place hard to access. This model is equipped with a 15.7 inch screw shaft and a guard grill on the bucket. The bucket is emptied from the bottom hatch in the middle of the bucket. Hatch opening is powered by a hydraulic cylinder controlled with an electric directional valve, operation from the driver's seat with an electric switch. The bucket is also equipped with a flexible emptying tube which mounts on the bottom hatch.

- **Easy and efficient way to make concrete in places where electricity is not available**
- **The mixed concrete is easy and effortless to transport and pour into desired place**
- **Self loading - sand can be taken to the bucket directly from the pile**
- **Concrete can be poured to over 6 feet height**

| | |
|--------------------------|-----------|
| Total width | 58.7 in |
| Screw shaft diameter | 15.7 in |
| Volume | 7.4 cu ft |
| Empty weight | 660 lb |
| Weight at max. capacity | 1750 lb |
| Unloading hatch diameter | 7.1 in |
| Emptying tube length | 53.1 in |
| Product no | A36473 |



| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable




Incompatible

Drum type concrete mixer

Digging and construction

Concrete mixing drum is a handy tool when you need to make concrete without electricity or when you need to transport or lift the concrete to a place that is hard to reach. Mixing is done hydraulically and emptying is done simply by tipping the drum forward.



- **Economical attachment for more occasional concrete mixing**
- **Easy way to make concrete in places where electricity is not available**
- **Ready mixed concrete is easy to transport and lift to desired place**

| | |
|------------|-----------|
| Volume | 2.8 cu ft |
| Operation | hydraulic |
| Weight | 120 lb |
| Product no | A2950 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |
| | | | | | | | | | | |

Disc scraper

Disc scraper is an excellent and cost efficient tool for removing carpet and floor tiles in demolition and refurbishing jobs. The durable disc takes off old carpet and tiles quickly and efficiently.



- **Efficient and economical carpet and floor tile remover**
- **Fits on all Avants**

| | |
|---------------|---------|
| Disc diameter | 22.0 in |
| Length | 37.8 in |
| Width | 22.0 in |
| Height | 20.0 in |
| Weight | 183 lb |
| Product no | A36910 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |
| | | | | | | | | | | |

Vibrating plate

Vibrating plate is designed for earth compacting and is easy to attach to an Avant. Compacting is easy and safe with the vibrating plate connected to Avant's quick attach plate – the operator is not exposed to vibrations or excessive noise.

- **Efficient compacting also in places where bigger compactors don't fit**
- **Fast and easy mounting on Avant**



| | |
|--------------|----------------|
| Weight | 330 lb |
| Plate size | 11.2 x 19.7 in |
| Impact force | 1985 lb |
| Impact rate | 2000 bpm |
| Product no | A21012 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |

Compatible
 Adaptable
 Incompatible

Asphalt grinder

The asphalt grinder, also called "cold planer" is an ideal attachment for asphalt road and pavement repairs and utility jobs. It grinds away the asphalt surface up to 3.15 in depth, making repair of potholes, utility cuts, small overlays and edge repairs fast and easy.

- **Powerful grinder for asphalt road and pavement repairs and utility jobs**
- **Hydraulic side shift 19.7 in as standard**



| | |
|---------------|-----------|
| Working width | 12.0 in |
| Operation | hydraulic |
| Weight | 575 lb |
| Product no | A21230 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |

Compatible
 Adaptable
 Incompatible

Submersible pump

Digging and construction

Submersible pump is a very useful attachment for situations where larger amounts of water or other fluids need to be drained from trenches, pits, wells etc. Pumping capacity is as high as 528 gal/min and fluid can be taken up from max. 65 ft depth. The pump is equipped with a 54 ft long discharge hose. The 32 ft long hydraulic hose kit is the same as for handheld tools.



- **Efficient pump for draining of water or other fluids from trenches, pits, wells etc.**
- **Fluid can be taken up from max. 65 ft depth**
- **Equipped with 54 ft long discharge hose**

| | |
|--------------------------|-------------|
| Pumping capacity max. | 528 gal/min |
| Pumping depth max. | 65 ft |
| Aux. hydr. oil flow max. | 10 gal/min |
| Width | 13.8 in |
| Height | 27.6 in |
| Weight | 44 lb |
| Product no. | A36708 |

Option:
Hydraulic hose kit, 32 ft, with multi-connector A36707

| | | | | | | | | | | |
|-----|-----|---------|------------|-----------|-----|-----|--------------|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |
| | | | Compatible | Adaptable | | | Incompatible | | | |

All-round grapple

Farming and horse stables

This versatile tool can be used for lifting and transporting of many different types of materials which cannot be handled with a normal bucket or pallet fork. The grapple is equipped with a hydraulic cylinder in the upper grapple part and it opens all the way up in vertical position. This, together with the pressing force of the cylinder, gives excellent loading and handling capabilities. Total width is 35.4 in - this allows traveling through narrow doorways and working in small spaces.



- **Simple and robust hydraulic grapple for handling of various materials**

| | | |
|---------|--------|------------|
| Width | Weight | Product no |
| 35.4 in | 143 lb | A110 |

| | | | | | | | | | | |
|-----|-----|---------|------------|-----------|-----|-----|--------------|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |
| | | | Compatible | Adaptable | | | Incompatible | | | |



Silage fork

A robust silage fork equipped with a powerful hydraulic cylinder, can be fitted on all Avant loader models. The strong blade type pins of the grapple penetrate into all types of feed. The fork has replaceable lower tines made of reinforced steel. The grapple goes up to vertical position and this, together with the powerful cylinder enables easy grabbing e.g. on a round bale.



Option:
Mounting plate which increases tipping angle by 17 degrees A36337
(only for special applications, risk of puncturing the front tires)

- Compact model, which is well suited for silage distributing in small and confined places.
- The front edges on the forks are rounded, which offers a smaller turning diameter.
- Updated 31.5 - 51.2 in models: tipping angle smaller as standard
- Mounting plate which increases tipping angle by 17 degrees is available as an option

| Width | Weight | Product no |
|---------|--------|------------|
| 31.5 in | 187 lb | A2868 |
| 35.5 in | 220 lb | A36299 |
| 41.3 in | 265 lb | A36313 |
| 51.2 in | 285 lb | A36319 |

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



XL Silage grab

The larger silage grab series is intended for Avant 500, 600 and 700 series loaders, with three different widths to match machines perfectly. The new series can carry up to 30 % more silage without losing visibility on the feeding table. Open grab construction on the top offers better visibility when the grab is open. Strong heavy duty construction with two cylinders. Forged bolt-on tines also on the top grab.

- Larger silage grab model
- The top grab construction is completely open from middle which improves visibility when driving while the grab is open.
- Top grab has two cylinders for improved compression power



| Width | Weight | Product no |
|---------|--------|------------|
| 43.3 in | 419 lb | A21385 |
| 51.2 in | 441 lb | A21384 |
| 59.1 in | 475 lb | A21380 |

Optional extras:
Mounting bracket which increases tipping angle by 17 degrees A34587

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |





Feeding table cleaning blade

This cleaning blade is specially designed for clearing the cattle feeding table before distributing new silage to the table. The cleaning blade can be mounted by driving the silage fork into the blade, no need to get out of the driver's seat which speeds up the cleaning process, because no attachment change is necessary. The cleaning blade has a rubber lip on the lower surface that ensures good cleaning result.

ATTENTION! Available only together with Avant silage forks.

- **The easiest way to clean the cattle feeding table**
- **Mounts on Avant silage forks: drive the fork into the blade with the grapple open and press the grapple down to lock the blade → no need to get out of the driver's seat.**



For silage fork

| | |
|----------------------|---------|
| Width | 47.2 in |
| Side extension width | 21.7 in |
| Weight | 110 lb |
| Product no | A2936 |

For XL silage grab

| | |
|----------------------|---------|
| Width | 65.0 in |
| Side extension width | 21.7 in |
| Weight | 165 lb |
| Product no | A35512 |

Optional extras:

Extra side extension 21.7 in A46337

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Silage dispenser

This dispenser bucket is equipped with hydraulically driven elevator in the bottom and discharging to both right and left side. Especially recommended for precision chopped silage and feeding stuffs made with feed mixers. The dispenser bucket can be filled like a normal bucket directly from floor level.

- **A quick and easy way to distribute silage**
- **The silage can be distributed on both sides of the bucket without making any adjustments**
- **The bucket can be tilted down to ground level and filled like a normal bucket**



| | |
|------------|------------|
| Volume | 23.0 cu ft |
| Width | 54.0 in |
| Weight | 530 lb |
| Product no | A21000 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |





Feed mover screw

Efficient way of moving uneaten feed back in front of the cattle. When moving, the screw mixes the feed and the fresh feed remains on top.

With the feed mover screw drive speed can be higher, 6 mph. Feed can be moved both to the right and to the left simply by changing the rotation direction. The plastic scraper blade at the rear of the attachment cleans the feeding table very efficiently.

- **Fast and easy way of moving feed to the animals**
- **Discharge in both directions**
- **High efficiency, also on larger farms**
- **Scraper blade cleans the feeding table efficiently**



| | |
|---------------|---------|
| Working width | 55.1 in |
| Total width | 64.4 in |
| Weight | 265 lb |
| Product no | A21506 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Silage block cutter

Powerful and robust silage cutters with two hydraulic cylinders. With the silage cutter you can easily cut silage directly from the silo and take it to the cattle. Cutting blades are made of special steel; they cut very efficiently and leave a clean and even surface in the silo. This prevents air getting into silage and warming up. Thanks to the open design of the cutting blade visibility during silage distribution is very good. Lower tines are made of hardened steel.

- **Strong and robust design, cuts efficiently also tightly packed silage**
- **39.4" cutter and 51.2" cutter**
- **Open design allows for good visibility also when distributing the silage**
- **Strong lightweight construction**
- **Tines made of hardened steel**



| | | |
|------------|---------|---------|
| Width | 39.4 in | 51.2 in |
| Weight | 540 lb | 617 lb |
| Product no | A21276 | A21257 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |





Carousel broom

The hydraulically operated carousel broom is a useful attachment when sweeping materials to the side or away from the wall. Rotates in both directions, can be angled manually to both sides by max. 57 degrees (42.9 in), which allows sweeping next to the wall. Carousel broom can be used for various sweeping tasks especially in farm environment.

- **Strong broom, moves materials efficiently**
- **Side shift allows brushing next to the wall also**
- **Rotates in both directions**
- **Can be turned manually to both sides, in different positions, by max. 57 degrees (42.9 in) – allows sweeping next to the wall also**
- **Equipped with replaceable 39.4 in diameter nylon brush**



| | |
|--------------------|----------|
| Width | 39.4 in |
| Broom diameter | 39.4 in |
| Turning angle max. | +/- 57 ° |
| Broom material | Nylon |
| Weight | 154 lb |
| Product no | A2971 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Round bale grab

With the round bale grab you can lift and transport wrapped silage bales, hay bales and other round bales without damaging the plastic wrapping or net. Sturdy, yet light construction allows best possible effective load (see the table below).

- **The round bale grab transports all wrapped bales without damaging the wrappings**
- **With Avant and bale grab you are able to pile three round bales on top of each other**



| | |
|------------------|----------------|
| Weight | 265 lb |
| Max. bale weight | |
| Avant 400 series | 880 lb |
| Avant 520 | 1215 - 1435 lb |
| Avant 528 | 1875 - 2095 lb |
| Avant 600 series | 2095 - 2315 lb |
| Avant 700 series | 2425 - 2645 lb |
| Max. grab width | 59.0 in |
| Bale diameter | 37.4 - 57.1 in |
| Product no | A21166 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |





Square bale grab

Square bale grab is designed for handling of wrapped silage bales, hay bales and other square bales without damaging the plastic wrapping or net.

- **Transport wrapped square bales without damaging the plastic**
- **Compact and robust design**



| | |
|------------------|----------------|
| Weight | 310 lbs |
| Max. bale weight | 2200 lb |
| Bale diameter | 31.0 - 47.0 in |
| Product no | A410798 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Bale handler

Bale handler is an economical way to handle wrapped bales, without damaging the plastic wrapping. Distance between the forks can be adjusted manually. Bale handler is a good choice if the bales can always be handled sideways and don't need to be grabbed.

- **Economical way to handle wrapped bales**
- **Adjustable fork width**
- **Useful attachment for situations where bales don't need to be grabbed**



| | |
|------------|---------|
| Width min. | 40.7 in |
| Weight | 183 lb |
| Product no | A36262 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |




Bale fork

With the round bale fork transporting and lifting of round bales is easy and safe. Square bale fork makes it easy and safe to transport and lift square bales.

Strong and simple construction ensures a long lifespan.

- **Easy and economical way to lift and transport bales**
- **Two models: for round and square bales**



| Model | Square bale fork | Round bale fork |
|----------|------------------|-----------------|
| Width | 39.6 in | 48.0 in |
| Length | 45.1 in | 45.3 in |
| Weight | 130 lb | 120 lb |
| Tines | 3 pcs | 2 pcs |
| Prod. no | A410225 | A410224 |

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Round bale splitter

Avant round bale splitter splits frozen bales which are otherwise hard to handle.

Splitting is fast and efficient thanks to the form of the cutting blade and the strong hydraulic cylinder.

The bale can also be transported with the splitter.

Wide and open design allows splitting of various size bales.

- **Efficient round bale splitter, splits frozen bales**
- **Bales can also be transported with the splitter, without splitting**
- **Wide and open design allows splitting of various size bales**



| | |
|------------------------|-------------------------|
| Splitting force | 48500 lb |
| Tines | 2 pcs long, 2 pcs short |
| Cutting blade length | 78.2 in |
| Total length | 80.7 in |
| Width | 49.2 in |
| Height with blade up | 86.6 in |
| Height with blade down | 38.6 in |
| Weight | 670 lb |
| Product no | A36199 |

| | | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i | 760i |
| | | | | | | | | | | | |





Bedding distributor bucket

The bedding distributor bucket is intended for distribution of different types of beddings. The bucket is equipped with a 11.8 in wide belt, which allows distribution of chopped straw, sawdust, peat, bark, wood shavings, sand and lime. Belt speed is steplessly adjustable.

The bucket is equipped with a mixing shaft which distributes the material evenly on the belt. Discharge to the left or to the right. Rubber scraper blade, designed for cleaning the floor grates, is available as an option. It mounts under the bucket.

- **Efficient distribution of various types of beddings**
- **Equipped with 11.8 in wide belt - belt speed steplessly adjustable by adjusting engine RPM's**
- **Discharge to the left or to the right**
- **Rubber scraper blade for floor cleaning available as an option**



| | |
|------------|----------------------------------|
| Volume | 28.3 cu ft |
| Belt width | 11.8 in |
| Belt speed | 0-33 ft/s, steplessly adjustable |
| Width | 55.1 in |
| Weight | 750 lb |
| Product no | A36532 |

Option: Rubber scraper blade A36704

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable




Incompatible

Manure fork

Farming and horse stables

Avant manure fork is a very useful attachment for handling of manure and similar materials. The strong tines penetrate into compacted manure and can carry a heavy load.

- **Strong fork for handling of manure and similar materials**
- **Equipped with bolt-on replaceable tines, made of high tensile forged steel**



| | |
|-------------|---------|
| Width | 43.3 in |
| Tine length | 39.4 in |
| Fork length | 43.7 in |
| Height | 16.3 in |
| Weight | 132 lb |
| Product no | A36038 |

| | | | | | | | | | | |
|--|-----|---------|--|-----|-----|--|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |
| Compatible | | | Adaptable | | | Incompatible | | | | |

Grain/flour dispenser bucket

Avant grain dispenser is a 10.6 cubic foot bucket equipped with a hydraulic motor and a 8" screw, designed for distribution of flour, crushed grain etc. Discharge to the right side.

The edge of the grain dispenser tilts all the way down so that loading from ground level is easy. The bucket is available in two versions: with discharge either to the right side or to the left side.

- **Easy distribution of flour, crushed grain etc.**
- **Self-loading when needed: loading from ground level like with a normal bucket is also possible**
- **Two versions available: discharge to the right or to the left**



| | |
|-------------------------------------|------------|
| Volume | 10.6 cu ft |
| Width | 43.3 in |
| Weight | 198 lb |
| Product no., discharge to the right | A1194 |
| Product no., discharge to the left | A36559 |

| | | | | | | | | | | |
|--|-----|---------|--|-----|-----|--|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |
| Compatible | | | Adaptable | | | Incompatible | | | | |



Push broom

Push broom is a handy and inexpensive broom for cleaning of smaller areas. Push broom has no rotating parts - it simply pushes the material in front of the broom.

Push broom can also be used when laying brick pavers. By pushing the filler sand sideways across the paving stones the sand will fall nicely between the stones.

- **An inexpensive and simple broom**
- **No rotating parts allows for less dust when brushing**
- **Works perfectly for horse stables, farms, other brushing applications**



| | | |
|------------|---------|---------|
| Width | 78.7 in | 51.2 in |
| Weight | 190 lb | 75 lb |
| Product no | A36453 | A34055 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



3-point hitch adapter

With the 3-point hitch adapter it is possible to move agricultural attachments with Avant. It makes moving your 3-point attachments to storage or for cleaning practical especially when space is limited and handling the implement with the tractor is difficult. Also the trailer ball hitches can be mounted on the 3-point hitch adapter.

- Easy way to handle 3-point attachments with Avant
- Equipped with CAT2 tractor hitch as standard - CAT1 mounting kit is available as an option
- Avant trailer ball hitches can also be mounted, as an option



Option:
 CAT1 mounting kit A418980
 Trailer ball hitch A417323
 Trailer ball hitch with towing pin A417337

| | |
|------------|--------|
| Type | CAT 2 |
| Weight | 125 lb |
| Product no | A36433 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |






Horse manure collector

Horse manure collector is a simple and economical way to collect horse manure. It works well on many surfaces (saw dust, horse arenas). Mounts directly on any Avant bucket.

- **Simple and economical way to collect horse manure**
- **Mounts on Avant general and light material buckets**



| | |
|------------|---------|
| Width | 37.4 in |
| Weight | 65 lb |
| Product no | A36292 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Front cultivator

Front cultivator can be used together with the horse arena harrow. It is especially useful in a more compacted arena or an outdoor riding area. It is equipped with large tines which loosen the soil and make harrowing of the arena easier. Equipped with two wheels in the front.

- **Efficient and easy way to loosen compacted soil**
- **Equipped with replaceable tines**
- **Can be mounted on all Avants**



| | |
|-----------------|---------|
| Width | 55.5 in |
| Length | 28.5 in |
| Height | 24.8 in |
| Number of tines | 7 pcs |
| Weight | 176 lb |
| Product no | A36555 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |






Horse arena harrow

The horse arena harrow is intended for leveling and loosening of horse arena riding surfaces. The harrow has two spring loaded tine rows which loosen the surface, a leveler that makes the surface completely even and a tilling roller that compacts the ground and leaves a finished surface perfectly suited for horse's hoof. The harrow doesn't damage the lower levels (understructure) of the riding surface.

The horse arena harrow features:

- A clearing shovel which takes away and levels the sand from the sides of the riding arena.
- A tilling roller that smoothens the harrowed ground and leaves a finished surface.
- A large wheel that protects the walls of the riding arena in case the harrow hits the wall.



Options:

- Manually operated support wheels in the rear (product no. A36593). Make it possible to tow the harrow away from the arena to desired place.
- Weights with handle, 64 lbs, which can be mounted on the harrow to increase weight and make harrowing more efficient. With two weights the harrow works on almost any surface. The weight is the same extra weight as on Avant loader, product no. A35957.

- **New model: no hydraulics required**
- **A professional harrow that makes it easy to keep the horse arena in top condition**
- **Can be adjusted for several kinds of riding surfaces**
- **Once the adjustments have been done the harrow is very easy to use**
- **Support wheels available as an option: the harrow can be lifted off the ground and towed to desired place**

| | |
|--------------------------------------|---------|
| Working width | 53.2 in |
| Weight (without 64 lb extra weights) | 365 lb |
| Product no | A21646 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Big bag transporter

With the big bag transporter you can lift and transport big bags safely and securely. This simple attachment makes loading of fertilizer or stacking big bags as easy as it can get.

- An inexpensive and safe way to handle big bags
- Lift hook can be adjusted in four different heights between 47 - 71 in



| | |
|------------------|----------------|
| Lift hook height | 47.0 - 71.0 in |
| Width | 39.4 in |
| Weight | 176 lb |
| Product no | A36221 |


| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Stone collecting bucket

The stone collecting bucket - also known as riddle bucket - is intended mainly for collecting stones from the fields after the field has been harrowed. With an Avant 400, 500, 600 or 700 series it is easy and fast to collect stones from nearby fields.

- **Easy and fast way to collect stones from fields**
- **Equipped with strong and durable bars**



| | | |
|--------------|---------|---------|
| Width | 41.3 in | 54.0 in |
| Bar diameter | 0.9 in | 1.2 in |
| Weight | 210 lb | 550 lb |
| Product no | A2999 | A415432 |

| Model | 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-------|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 41.3 | | | | | | | | | | | |
| 54.0 | | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Compressor

Makes it possible to have compressed air anywhere you go. Creates maximum 105 gal/min at 115 PSI pressure. Can be used for running power tools and in circumstances where electricity is not available.

- **Easy way to get compressed air e.g. for pneumatic power tools**
- **Makes it possible to fill large tires (agricultural & construction machines for example) in places where electricity is not available**
- **Fast cleaning of big machines with compressed air: combine, construction machinery etc.**
- **With rear mounting the compressor is always available, and other attachments can be mounted in the front**



| Mount | Product no |
|-------|------------|
| Front | A35409 |
| Rear* | A35456 |

*) Rear mounting set is included, requires double acting rear auxiliary hydraulics from the loader (Rear mounting is not available for 200 series)

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |





Pressure washer

Powerful pressure washer with 65 foot hose reel; easy to take anywhere with the Avant. Creates maximum 8 gal/min water flow and 2900 PSI pressure. Can be connected directly to a water hose or a barrel.

Can suck water via inlet hose from as much as 10 feet below the level where the unit is. This is a very useful feature when taking water from a tank, reservoir, lake etc.

- **Powerful washer with high max. water flow and pressure**
- **Can be connected directly to tap, or with the inlet hose take water from as much as 10 ft below ground level**
- **Equipped with 65 foot hose reel and washing gun**
- **With rear mounting the washer is always available, and other attachments can be mounted in the front**



| Mount | Max. water flow | Product no |
|-------|-----------------------|------------|
| Front | 8 gal/min at 2900 PSI | A35411 |
| Rear* | 8 gal/min at 2900 PSI | A35457 |

*) Rear mounting set is included, requires double acting rear auxiliary hydraulics from the loader (Rear mounting is not available for 200 series)

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible

Handheld tools

Even though Avant is the tool carrier and normally the attachments are mounted on the attachment coupling plate and operated from the driver's seat, there can be situations where handheld hydraulic tools are practical: in places where the operator needs to do the work further away from the Avant. For example when the work site is in such a tight spot that it cannot be accessed with the Avant directly.

Handheld tools are equipped with a 32 ft long hose kit (2 pcs hoses, pressure-return) with multi-connector, for mounting on the standard front auxiliary hydraulics outlet of the loader. If necessary, handheld tools can also be connected in the optional rear auxiliary hydraulics outlet.

Rock drill

The lightweight rock drill is designed for drilling blast, anchor and rock-splitting holes. Used for example by contractors and utilities who want convenient and efficient drilling without large compressors. With standard integral steel, it drills diameters of up to 2" using hydraulic power for impact and rotation. A small additional compressor is needed for flushing, for instance the Avant compressor A35456 can be mounted in the rear and operated at the same time as the rock drill in the front.

| | |
|---------------------------|----------------|
| Weight, incl. hoses | 57.3 lb |
| Service weight | 62.8 lb |
| Impact rate (at 25 l/min) | 2550 blows/min |
| Revolutions | 320 - 400 rpm |
| Torque | 48 ft lbf |
| Product no. | 66194 |
| Rod, tapered, 15.75 in | 66200 |
| Drill bit 1.3 in | 66199 |



Hydraulic breaker

This medium weight, multipurpose breaker is commonly used with 5" asphalt chisels for road building maintenance applications, but also works well in brickwork, frozen soil and concrete.

| | |
|---------------------------------|-----------------------|
| Impact rate | 1500 - 2100 blows/min |
| Weight, incl. hoses | 61.7 lb |
| Length | 28.9 in |
| Product no. | 66195 |
| Chisel, narrow 1.26 in x 6.3 in | 66198 |



Core drill

Core drill is intended for all hand-drilling jobs and where there is no room for drill stands. It drills in reinforced concrete and asphalt up to 8" diameter. Due to the hydraulic control of the drill torque, the core drill gives very low kickback should drill bits jam. This helps operator to maintain control, even when working on holes of 8" in diameter.

Core drill is used by professionals in a wide range of applications including building renovation and utility works. Core drill helps to install drainage, sewer and water pipes, plus cable and ventilation ducts where large and deep holes are needed. Core sampling in asphalt roads is another application for this drill. Works efficiently also in underwater applications.

Diamond blades and core bits need a small but constant supply of water to flush away slurry and to depress dust. Where water is available, taps can be used and water flow can be regulated on the tool. On remote sites where there is no water supply, a small pressurized water container is available.



Handheld tools

| | |
|---|---------------|
| Weight, incl. hoses | 21 lb |
| Service weight, incl hoses and Ø 4.4 inc tool | 28.7 lb |
| Length, without drill | 16.3 in |
| Revolutions | 600 - 900 rpm |
| Drill Diameter | 2 - 8 in |
| Product no. | 66192 |
| Diamond core bit 4.4 in | 66196 |

Cut-off saw

The powerful, light and compact saw makes a quick job of cutting concrete, asphalt and steel. The simple hydraulic design with direct drive provides high productivity, while reducing maintenance. The compact, slim design and open cutting face gives a good view to the work. With the help of a lightweight cart you can use the saws for floor, road and other light surface jobs. And the saw works in underwater works as well.



Diamond blades and core bits need a small but constant supply of water to flush away slurry and to depress dust. Where water is available, taps can be used and water flow can be regulated on the tool. On remote sites where there is no water supply, a small pressurized water container is available.

Used with:

- Dry and wet diamond discs
- Abrasive steel cutting discs

| | |
|---------------------------|-----------------|
| Cutting depth | max. 6.3 in |
| Weight, incl. hoses | 28.7 lb |
| Service weight, incl disc | 33.1 lb |
| Revolutions | 2000 - 4000 rpm |
| Speed | 137 - 278 ft/s |
| Product no. | 66193 |
| Diamond disc 16" | 66197 |

Option: Hose kit, 2 pcs 32 ft hoses, for handheld tools

A36707



Winch

The Avant hydraulic winch enables towing of all kinds of objects (e.g. logs, poles, boats) from places where you cannot drive with the machine.

The winch is equipped with a safety net, 100 feet of cable and a towing hitch. It is powered by a powerful hydraulic motor and mounts on Avant's quick attach plate.

Use of the winch is simple, one person can easily handle it. The auxiliary hydraulics lever is switched to continuous flow from the driver's seat, which releases the cable drum so that the cable can be pulled out by hand. When the cable is attached to the desired object, operator returns to driver's seat and turns the auxiliary hydraulics lever into opposite direction and the winch begins to reel in the cable.

- **Powerful and compact hydraulic winch for various tasks**
- **The winch is mounted directly on Avant's quick attach plate, so you are also able to use the boom for lifting materials with the winch.**



| | |
|--------------------|------------|
| Max. Pulling power | 2200 lb |
| Max. Reeling speed | 7.5 ft/sec |
| Wire length | 100 ft |
| Weight | 231 lb |
| Product no | A33130 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |





Tree shear

Avant tree shear is an efficient and useful tree cutter, intended for forest thinning, tree clearance and similar jobs where smaller trees need to be cut. The strong grapple takes a firm grip of the tree trunk and a hydraulic cylinder pushes the cutting blade against the trunk and cuts it. The tree is then easy and fast to move away with Avant. If needed, the cutting blade can be turned 180 degrees to point backwards. This means it doesn't cut and the unit can be used as a grapple only.

- **Powerful tree cutter for max. 7.5 in diameter trees**
- **Excellent tool for forest thinning, tree clearing**
- **Thanks to the strong grapple the tree is easy to take away with Avant**
- **Can also be used as a grapple only, by turning the cutting blade to point backwards**

| | |
|-----------------|-------------|
| Tree diameter | max. 7.5 in |
| Grapple opening | 30.3 in |
| Weight | 243 lb |
| Product no | A35831 |



| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Log grab, heavy duty

A strong log grab for customers who need to move tree trunks, logs etc. The grab takes a firm grip on the wood and the lower tines are also better formed for grabbing bigger tree trunks.

- **Heavy duty design allows grabbing of larger logs**
- **Grabbing and transporting of bigger stones and similar objects also possible**



| | |
|------------|---------|
| Width | 33.3 in |
| Height | 39.0 in |
| Weight | 396 lb |
| Product no | A415691 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |





Log grab

The Avant log grab mounts on Avant pallet fork. With the log grab you can lift and transport single logs or smaller timber bundles. The grab is equipped with a powerful hydraulic cylinder and can therefore also lift bigger stones, as well as branches, fence poles and similar objects.

Requires also:

Pallet fork 33.5" (A21047)

Pallet fork 43.3" (A21039)

Pallet fork 47.2" (A36589)

- **Easy mounting on pallet fork**
- **Basic attachment for fencing and forest work**
- **Grabbing and transporting of stones and similar objects also possible**

| Max. diameter | Min. diameter | Weight | Product no |
|---------------|---------------|--------|------------|
| 35.4 in | 7.0 in | 110 lb | A33503 |

Assembled to pallet forks



| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible



Timber grab

Timber grab is an attachment that allows you to grab tree trunks, branches, wood waste and transport them both lengthwise and crosswise. This makes it possible to pass through narrow places also with long logs and enables loading on trailer or on a pile in any direction. Timber grab is available either with a hydraulic rotator or as freely rotating version. The grab with hydraulic rotator is equipped with an electric solenoid valve for selection between grab opening/closing and rotator, operated from the driver's seat.

- **Versatile grab for transporting and loading of tree trunks, branches, curb stones etc.**
- **Rotating grab allows transporting also lengthwise - makes it possible to pass through narrow places with long logs and facilitates work in dense forest**
- **Available with hydraulic rotator or as freely rotating version**



| Rotation type | Freely rotating | Hydraulic rotation |
|--------------------------|-----------------|--------------------|
| Grapple opening diameter | 31.5 in | 31.5 in |
| Weight | 181 lb | 223 lb |
| Product no | A36531 | A36491 |

The optional attachment control switch pack is recommended with timber grab with hydraulic rotator.

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |



Tilt adapter

Avant tilt adapter is mounted between the attachment and the loader's attachment coupling plate. With it the attachment can be tilted sideways, and makes it possible to:

- Make different forms to the ground with a bucket or leveler
- Keep pallet fork level when you are driving on surfaces with gradient
- Load pallets that are on uneven ground
- Level ground on uneven surfaces
- With the 90 degree tilt adapter rotate the attachment as much as 90 degree


There are two tilt adapters available:

- Tilt adapter with max. 12.5 degree tilting in both directions. It is intended for buckets, leveler and pallet fork – for jobs where tilting is a must but the tilting angle doesn't have to be greater than 12.5 degrees.
- Tilt adapter with max. 90 degree rotation, or 45 degree tilting in both directions. It is useful in applications where the attachment needs to be rotated more in order to get the job done: with grabbing tool (rotating of barrels etc.), artificial turf attachment (to fit through narrow doors) etc.

The hydraulic cylinder of the 90 degree tilt adapter can be mounted in two different positions, which gives two tilting angles: either 45° tilting in both directions, or 90° rotation in one direction. The tilt adapter is intended mainly for non-hydraulically operated attachments, but with the optional second auxiliary hydraulics outlet in the front it is possible to use hydraulically driven attachments like a 4 in 1 bucket, pallet fork with hydraulic fork adjustment, grabbing tool and artificial turf attachment at the same time.

- **Makes it possible to tilt the attachment sideways to grade the ground with a bucket or leveler, or load pallets on uneven ground with pallet fork**
- **Mounts between the attachment and the quick attach plate of the loader**
- **Two models: with max. ± 12.5° tilting or with max. 90° / ± 45° rotation**

Options




| | | |
|------------|-----------|---------------|
| Max. tilt | +/- 12.5° | 90°, or ± 45° |
| Weight | 143 lb | 187 lb |
| Product no | A34148 | A36505 |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |

Compatible
 Compatible
 Incompatible

Receiver hitch

Rear mounted 2 inch receiver hitch.



| | |
|----------------|------------|
| Model | Product no |
| Receiver hitch | HH2INREC |

| | | | | | | | | | | |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
| | | | | | | | | | | |

Compatible
 Adaptable
 Incompatible

Adapter plate

Avant offers a variety of original adapter plates, which can be welded directly onto:

- An attachment you have developed yourself.
- An object you wish to lift securely with Avant

All original Avant adapter plates will fit, which saves a lot of time consuming measuring and adjusting work from you.

Options



| Model | Product no |
|---|------------|
| Quick attach brackets, 400/500/600/700 series | A31566 |
| Adapter plate 0.4 in 400/500/600/700 series | A2471 |
| Adapter plate 0.8 in 400/500/600/700 series | A2472 |

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible

Skid-Steer Attachment Mounting Adapters



Universal Skid-Steer Attachment Mounting Adapter

Product no. BER-QTFS



MT Skid-Steer Attachment Mounting Adapter

Product no. BER-QTMT



Mini Skid-Steer Attachment Mounting Adapter

Product no. BER-QTMINI

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible

Attachment control switch pack

Optional extra with which electric functions of the attachment (electric throwing height adjustment on snow blower, opening of lawn mower collector lid, control of water spraying system on the broom etc.) are controlled.


The control switch pack can be mounted both on the standard boom control lever and on the optional electric 6 or 8 function joystick. It consists of the switches and the wiring with a socket that is mounted on the auxiliary hydraulics multi-connector.

The corresponding electric wire and socket of the attachment is mounted on the attachment multi-connector. This way both the hydraulic hoses and the electric wire of the attachment are connected quickly and effortlessly at the same time.

Operation of the attachment's electric functions is very convenient and easy, because the toggle switches are mounted on the control lever within reach of your right thumb.

| Model | Product no |
|----------------|------------|
| 200 series | A36880 |
| 400-700 series | A36878 |

Additional products



| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible

Tie down bracket

Tie down bracket for mounting on the wheel hub.



| Model | Product no |
|------------------|------------|
| Tie down bracket | A421206 |

| 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| | | | | | | | | | | |



Compatible



Adaptable



Incompatible

Additional products



A418746 Tie down bracket

A simple bracket, that makes it easier to tie down machines during transport. Fits either to the back of the machine or to side of rear frame. Can be mounted also between rear frame and trailer coupling, which allows the use of it even if a trailer coupling is mounted



A418706 Lifting sling kit ROPS

With this kit you are able to lift 400-700 series machines safely and legally with a crane or similar hook lifting device. Kit holds all necessary materials and instructions to lift a machine.



A417352 Lifting sling kit LX/DLX

With this kit you are able to lift 400-700 series machines safely and legally with a crane or similar hook lifting device. Kit holds all necessary materials and instructions to lift a machine.



A35237 Mudguards rear, pair (528 & 600)

- only on 26x12.00-12 and 320/60-12
- standard with DLX cab, if applicable
- if adding to machine without DLX cab, rear side panels need to be changed



A36573 Equipment box (700 series)

The equipment box allows you to transport tools, supplies, spare fuel tank etc. at the back of the machine. It has a specially designed place for a spade and a chain saw. The box is bolted directly onto the rear counter weight of the loader and it is possible to use the trailer hitches on the back of the box. The lid can be locked with a pad lock if necessary.

Filter kits


| Product no: | Description |
|-------------|--|
| U00001 | 50 Hour Service Kit 420/520 |
| U00002 | 50 Hour Service Kit 528 |
| U00003 | 50 Hour Service Kit 630/635/640 |
| U00004 | 50 Hour Service Kit 745/750 |
| U00005 | 50 Hour Service Kit 755i/760i |
| U00006 | 50 Hour Service Kit 220/225/225 LPG |
| A46683 | 200 Hour Service Kit 220 |
| A420536 | 200 Hour Service Kit 225/225 LPG |
| A416943 | 200 Hour Service Kit 420/520 (for SN's after 70169) |
| A48036* | 200/400 Hour Service Kit 528 |
| A410961* | 200/400 Hour Service Kit 630/635/640 |
| A410784* | 200/400 Hour Service Kit 745/750 |
| A418900 | 400 Hour Service Kit 755i/760i |




* Any machine manufactured after 1/1/2015 has a service interval of 400 hours

Additional products


Multi-connector System



Multi-connector Pressure-Return
65251




Multi-connector Pressure-Tank line
65371



Multi-connector Pressure-Return-Tank line
65250



Flat Faced coupling kit to connect skidsteer Hydraulics to
Avant Multi-connector System
CE565-9656



Multi-connector Parking on
attachment
A418927

Wheels & Tires




Wheel, complete (tire + rim)

| Product no: | Size | Tread | Bolt pattern | 220 | 225 | 225 LPG | 420 | 520 | 528 | 630 | 635 | 640 | 755i | 760i |
|-------------|-------------------------------|-------|--------------|-----|-----|---------|-----|-----|-----|-----|-----|-----|------|------|
| 66231 | 20 x 8.00-10 TR | 4 | 4 | std | std | std | | | | | | | | |
| 66252 | 20 x 8.00-10 GR | 6 | 4 | std | std | std | | | | | | | | |
| 65412 | 5.00 x 10 TR | 1 | 6 | | | | y | | | | | | | |
| 65046 | 23 x 8.50-12 TR | 2 | 6 | | | | std | | | | | | | |
| 65045 | 23 x 8.50-12 GR | 6 | 6 | | | | std | | | | | | | |
| 65995 | 23 x 8.50-12 TR | 2 | 5 | | | | | y | y | | | | | |
| 65994 | 23 x 8.50-12 GR | 6 | 5 | | | | | y | y | | | | | |
| 65048 | 23 x 10.50-12 TR | 4 | 6 | | | | y | | | | | | | |
| 65047 | 23 x 10.50-12 GR | 6 | 6 | | | | y | | | | | | | |
| 65997 | 23 x 10.50-12 TR | 4 | 5 | | | | | std | std | | | | | |
| 65996 | 23 x 10.50-12 GR | 6 | 5 | | | | | std | std | | | | | |
| 65212 | 26 x 12.00-12 GR | 6 | 10 | | | | | y | y | std | std | std | std | |
| 65739 | 26 x 12.00-12 TR | 4 | 10 | | | | | y | y | std | std | std | | |
| 65414 | 27 x 8.50-15 TR | 2 | 10 | | | | | y | y | y | y | y | y | y |
| 65224 | 320/60-12, HD-wheel TR | 4 | 10 | | | | | y | y | y | y | y | std | |
| 65787 | 26.5 x 14.00-12 GR | 3 | 10 | | | | | | | | | | y | y |
| 65506 | 320/55-15 TR | 4 | 10 | | | | | | | | | | y | y |
| 65459 | 320/55-15 GR | 5 | 10 | | | | | | | | | | y | y |
| 65958 | 400/50-15 TR | 4 | 10 | | | | | | | | | | | std |
| 66257 | 400/50-15 GR | 6 | 10 | | | | | | | | | | | std |
| 65959 | 31 x 15.50-15 GR | 3 | 10 | | | | | | | | | | | y |

Tire tread patterns



1




2



3



4



5



6



AVANT[®]

Avant Tecno USA Inc.

3020 Malmo Drive

Arlington Heights, IL 60005

847.380.9822 phone

847.380.9823 fax

e-mail: sales@avanttecnousa.com

AVANT has a policy of continuing improvement,
and retains the right to change specifications without notice.
© 2016 AVANT Tecno Oy. All rights reserved.

www.avanttecnousa.com